The new degree of comfort."

# Professional *Prestige®* electric water heaters offer a diagnostic system with leak protection and a 12-year warranty

### **Efficiency**

- .93 UEF
- Isolated tank design reduces conductive heat loss
- Dual 5500 watt stainless steel heating elements

#### **Performance**

- FHR: 56 63 gallons based on gallon capacity
- Recovery: 25 GPH at a 90° F rise\*\*

# **Super Sentinel Diagnostic System**

- Simple easy to read diagnostics
- Controls multiple operating modes
- Digital thermostat setting
- Built-in water sensor alert with audible alarm and service notifications



- EcoNet® WiFi-connected†
   technology and free
   mobile app gives users
   control over water
   systems, allowing for
   customizable temperature, vacation
   settings, energy savings and system
   monitoring at home or away.
   Visit Rheem.com/EcoNetConnect
- Water sensor detects water outside of the unit and sends an alert via the free EcoNet® mobile app to the homeowner
- EcoNet® WiFi Kit included

#### **Features**

- High performance and lower operating cost
- Compliant with many electric utility incentive programs
- Premium grade anode rod provides long-lasting tank protection
- Electric junction box located above heating elements for easy installation
- Over-temperature protector cuts off power in excess temperature situations

#### Plus...

- EverKleen<sup>™</sup> self cleaning device fights harmful sediment build-up with a high-velocity spiraling water stream – helps operating efficiency by saving energy, money and improving tank life
- Enhanced-flow brass drain valve
- Temperature and pressure relief valve included
- Low lead compliant

#### Warranty

- 12-Year limited tank and parts warranty\*
- \*See Residential Warranty Certificate for complete information
- †WiFi broadband internet connection required

Units meet or exceed ANSI requirements and have been tested according to D.O.E. procedures. Units meet or exceed the energy efficiency requirements of NAECA, ASHRAE standard 90, ICC Code and all state energy efficiency performance criteria.



# Professional Prestige

40 and 50-Gallon Capacities 240 Volt AC/Single Phase Electric







See specifications chart on back.

## Professional Prestige® Electric Specifications


DESCRIPTION				FEATURES		ROUGHING IN DIMENSIONS (SHOWN IN INCHES)				ENERGY INFO.
T Y P E	NOMINAL GALLON CAPACITY	RATED GALLON CAPACITY	MODEL NUMBER	UEF FIRST HOUR RATING G.P.H.	RECOVERY IN G.P.H. 90° F RISE	TANK HEIGHT A	HEIGHT TO WATER CONN. B	DIAMETER C	APPROX. SHIP WT. (LBS.)	UNIFORM ENERGY FACTOR (UEF)
Tall	40	36	PROPE40 T2 RH95 EC2	56	25	60-3/4	63-5/8	18-1/4	105	0.93
Tall	50	45	PROPE50 T2 RH95 EC2	63	25	58-5/8	61-5/8	20-1/4	121	0.93

Uniform Energy Factor and rated gallon capacity based on Department of Energy (DOE) requirements.

Super Sentinel not available on single element models, available on dual element models only. Super Sentinel not available in excess of 5 kW on 208 V models.

• Heaters furnished with standard 240 volt AC, single phase non-simultaneous wiring, and 5500 watt upper and lower heating elements.

\*\*Recovery = wattage/2.42 x temp. rise °F. Example:  $\frac{5500W}{2.42 \times 90^{\circ}}$  = 25 GPH



₩ Water

WATER CONNECTIONS ALL 3/4" N.P.T.

In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice. Rheem Water Heating • 1115 Northmeadow Parkway, Suite 100

INTEGRATED HOME COMFORT

<sup>\*\*</sup>Recovery calculations used are based on 5500 watt elements used in non-simultaneous operation.