Atmospheric Water Heaters



Professional *Achiever Plus*™ Atmospheric gas water heaters are engineered for more hot water at a low operating cost

Efficiency

- .62 EF
- More hot water at a low operating cost

Performance

- FHR: 68 to 83 gallons for natural gas
- Recovery: 36.4 to 40.4 gallons at a 90 degree rise, based on model

Guardian System[™] & Sensor

- Exclusive air/fuel shut-off device
- Maintenance free no filter to clean





Combustion Shut-off System

Flame Arrestor Plate

Low Emissions

- Eco-friendly burner, low NOx design
- Meets 40 ng/J NOx requirements

Longer Life

 Rheem exclusive R-Tech (resistored) anode rod provides long-lasting tank protection

High Altitude Compliant

- All models certified up to 6,000 ft. above sea level
- Some models certified up to 10,200 ft. above sea level, check factory for listings

Plus...


- Easy to light no matches required
- EverKleen[™] patented system fights sediment build-up
- Enhanced flow brass drain valve
- Temperature and pressure relief valve included
- Low lead compliant
- Standard replacement parts

Warranty

- 8-Year limited tank and parts warranty*
- With ProtectionPlus[™] the 8-year limited tank warranty becomes 12-year

*See Residential Warranty Certificate for complete information

Units meet or exceed ANSI requirements and have been tested according to D.O.E. procedures. Units meet or exceed the energy efficiency requirements of NAECA, ASHRAE standard 90, ICC Code and all state energy efficiency performance criteria.





Professional Achiever Plus Atmospheric

40 and 50-Gallon Capacities Up to 40,000 Btu/h Natural and LP Gas







myruud.com/proclub

		DESCRIPTION	FEATURES					ROUGHING IN DIMENSIONS (SHOWN IN INCHES)									ENERGY INFO.
T Y P	GAL.	MODEL		IPUT IN s. BTU/H	RECOV G.P.H. 9		FIRST HOUR DEL. G.P.H.	HT. TO VENT	TANK HT.	DIAM.	HT. TO GAS CONN.	VENT	WATER CONN. CNTR.	HT. TO SIDE T&P VALVE	WATER CONN. SIZE	SHIP. WT.	ENERGY FACTOR
E	CAP.	NUMBER	NAT.	LP	NAT.	LP	NAT.	A	В	С	D	E	F	G	Н	(LBS)	NAT.
Tall	40	PRO+G40-40N RU62†	40	-	40.4	-	68	63-1/4	60	19-1/2	14	3 or 4	8	53-1/2	3/4	135	0.62
Tall	40	PRO+G40-36P RU62	-	36	-	36.4	-	63-1/4	60	19-1/2	14	3 or 4	8	53-1/2	3/4	135	-
Tall	50	PRO+G50-40N RU62†	40	-	40.4	-	83	62-1/2	59-1/4	21-1/2	14	3 or 4	8	52-1/2	3/4	165	0.62
Tall	50	PRO+G50-36P RU62	-	36	-	36.4	-	62-1/2	59-1/4	21-1/2	14	3 or 4	8	52-1/2	3/4	165	-
Short	40	PRO+G40S-40N RU62†	40	-	40.4	-	72	54	50-1/2	23	14	3 or 4	8	44	3/4	135	0.62
Short	40	PRO+G40S-36P RU62	_	36	_	36.4	_	54	50-1/2	23	14	3 or 4	8	44	3/4	135	_

Energy Factor based on D.O.E. (Department of Energy) test procedures

In keeping with its policy of continuous progress and product improvement, Ruud reserves the right to make changes without notice.