



SALES FACT SHEET

ROCA-*P: Highboy Series**
ROLA-*P: Lowboy Series**
 Input Ratio from
84 to 175 kBTU
[24.61 to 51.28 kW]



Ruud *Achiever*® Series Highboy & Lowboy Oil Furnaces with PSC/Direct Drive Motor

Features

- The Ruud *Achiever*® Series upflow oil furnace is for installation in properly ventilated utility rooms, closets or alcoves.
- Direct Drive blower assemblies for heating and air conditioning applications
- 10-gauge primary and 14-gauge secondary heat exchanger
- Front cleanout ports extend through front wall for accessibility
- Efficiencies up to 85.9%
- Front or rear flue Lowboy available
- All furnaces have standard Honeywell controls
- Available with Beckett, Riello Carlin burners
- Extended vestibule on all units

GENERAL TERMS OF LIMITED WARRANTY

Ruud will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

PartsFive (5) Years
 Oil Heat ExchangerLimited Lifetime

Model	Lowboy ¹										Highboy									
	ROLA-070P					ROLA-115P					ROCA-070P					ROCA-115P				
Static Press. In. W.C. ² 1 ton = 400 CFM	0.2	0.5	0.2	0.5	0.2	0.5	0.2	0.5	0.2	0.5	0.2	0.5	0.2	0.5	0.2	0.5	0.2	0.5	0.2	0.5
CFM Hi Speed	1903	1661	1903	1661	1903	1661	2466	2072	2466	2072	1745	1480	1745	1480	1745	1480	2283	2007	2283	2007
CFM Med Hi Speed	1711	1485	1711	1485	1711	1485	2150	1859	2150	1859	1550	1343	1550	1343	1550	1343	2130	1832	2130	1832
CFM Med Lo Speed	1547	1355	1547	1355	1547	1355	1839	1610	1839	N/R	1376	1175	1376	1175	1376	N/R	1901	1644	1901	N/R
CFM Lo Speed	1399	1227	1399	1227	1399	N/R	1600	N/R	N/R	N/R	1250	1043	1250	N/R	1250	N/R	1717	1501	N/R	N/R
Shipping Weight	323					362					298					347				

1. Specify front or rear flue on Lowboy models.
2. Additional Specifications available upon request.

Price	Starting at:
	\$

[] Designates Metric Conversions

