

RUUD SALES FACT SHEET

R802P- SERIES 80% A.F.U.E.† Models with Input Rates of 50 to 150 kBTU [14.7 to 44 kW]



GENERAL TERMS OF LIMITED WARRANTY*

Ruud will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Heat ExchangerLimited Lifetime Conditional Parts

Department of Energy test procedures.

*For complete details of the Limited and Conditional Warranties, including applicable terms and conditions, contact your local contractor or the Manufacturer for a copy of the product warranty certificate.

Ruud *Achiever Plus*™ Series Upflow/Horizontal Gas Furnace

Features

- 80% residential Gas Furnace CSA certified
- Two stages of operation to save energy and maintain optimal comfort level.
- 3 way multi poise design UF / HZ
- PlusOne[™] Diagnostics 7 Segment LED all units
- PlusOne[™] Ignition System DSI for reliability and longevity
- Heat exchanger is removable for improved serviceability. Aluminized steel construction provides maximum corrosion resistance and thermal fatigue reliability.
- Solid doors provide quiet operation
- Solid bottom
- Insulated blower compartment
- Low profile 34" cabinet ideal for space constrained installations
- Blower shelf design serviceable in all furnace orientations
- Hemmed edges on cabinets and doors
- 1/4 turn door knobs for tool less access
- Integrated Control board features dip switches for easy system set up
- QR codes for quick access to product information from your smart phone or tablet

MODEL	INPUT- BTU/HR [kW] ①	HEATING CAPACITY BTU/HR [kW]	HEATING CFM @ .2" [.049 kPa] W.C. E.S.P. [L/s]	COOLING CFM @ .5" [.124 kPa] W.C. E.S.P. [L/s]	APPROX. SHIPPING WEIGHT (LBS.) [kg]	PRICE
R802PA050314M*A	50,000 [15]	40,000 [12]	1132 [534]	1250 [590]	110 [50]	
R802PA075417M*A	75,000 [22]	60,000 [18]	1542 [728]	1650 [780]	125 [57]	
R802PA100521M*A	100,000 [29]	80,000 [23]	1883 [889]	1800 [850]	140 [64]	
R802PA125524M*A	125,000 [37]	100,000 [29]	1774 [837]	1750 [825]	150 [68]	
R802PA150524M*A	150,000 [44]	120,000 [32]	1891 [892]	1900 [900]	160 [73]	

Note: Above data and specs are for upflow models.

[] Designates Metric Conversions













RUUD SALES FACT SHEET

R802P UPFLOW/HORIZONTAL						
Description	Part No.	Price				
External Bottom Filter Rack (Upflow/Horizontal) Rack	RXGF-CB					
External Side Filter Rack	RXGF-CD					
Indoor Coil Casing	RXBC-D14A1					
Indoor Coil Casing	RXBC-D17A1					
Indoor Coil Casing	RXBC-D21A1					
Indoor Coil Casing	RXBC-D21B1					
Indoor Coil Casing	RXBC-D24A1					
Solid Bottom Kit	RXGB-D14					
Solid Bottom Kit	RXGB-D17					
Solid Bottom Kit	RXGB-D21					
Solid Bottom Kit	RXGB-D24					