

RUUD SALES FACT SHEET



ACHIEVER[®] Series

Featuring Earth-Friendly R-410A Refrigerant



RQNM-

13 SEER Series

Nominal Sizes 2-5 Tons [7-17.6 kW]

RQPM-

14 SEER Series

Nominal Sizes 2-5 Tons [7-17.6 kW]

GENERAL TERMS OF LIMITED WARRANTY

Ruud will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Compressor

13 SEER, 1 Phase, Residential Applications	Eight (8) Years
14 SEER, 1 Phase, Residential Applications.....	Ten (10) Years
13 & 14 SEER, Commercial Applications.....	Five (5) Years
Any Other Part	Five (5) Years
1 Phase, Residential Applications.....	Five (5) Years
1 & 3 Phase, Commercial Applications.....	One (1) Year

Features

The Ruud *Achiever Series*[®] RQNM- & RQPM- Package Heat Pumps can provide year-round heating and cooling comfort for residential, multi-family and light commercial applications.

The following additional features, plus its energy-saving characteristics, make the RQNM- & RQPM- Package Heat Pumps an excellent choice for new construction or upgrading your present system.

- Scroll Compressor
- Copper Tube/Aluminum Fin Coils
- Powder painted louvered steel cabinet protects coil from damage
- Painted Base Pan
- Demand Defrost Control
- Non-Cycling Reversing Valve
- Gauge Ports
- Control box is fully accessible
- Power and control wiring are kept separate
- Certified and rated under ARI Standard 240
- U.L. listed
- Factory run tested prior to shipment

<u>R</u>	<u>Q</u>	<u>N</u>	<u>M</u>	<u>—</u>	<u>A</u>	<u>036</u>	<u>J</u>	<u>K</u>	<u>010</u>
RUUD	PRODUCT CLASSIFICATION	EFFICIENCY DESIGNATION (STANDARD)	DESIGN SERIES		FUTURE TECHNICAL VARIATIONS	NOMINAL COOLING CAPACITY	ELECTRICAL DESIGNATION	DRIVE PACKAGE	HEATING CAPACITY (FACTORY INSTALLED)
	Q = PACKAGE HEAT PUMP	N = 13 SEER P = 14 SEER	M = R-410A			024 = 24,000 BTU/H [7.03 kW] 030 = 30,000 BTU/H [8.79 kW] 036 = 36,000 BTU/H [10.55 kW] 042 = 42,000 BTU/H [12.31 kW] 048 = 48,000 BTU/H [14.07 kW] 060 = 60,000 BTU/H [17.58 kW]	J = 208-230V— 1PH—60 Hz C = 208-230V— 3PH—60 Hz (13 SEER ONLY)	K = DIRECT DRIVE	000 = No Resistance Heat 005 = 05 KW Resistance Heat 007 = 07 KW Resistance Heat 010 = 10 KW Resistance Heat 015 = 15 KW Resistance Heat 020 = 20 KW Resistance Heat

Price

Starting at:
\$

