



SALES FACT SHEET



Featuring
New Industry Standard
R-410A Refrigerant **R-410A**



13PJL SERIES

Features

- Coils constructed with copper tubing and enhanced aluminum fins
- Includes factory installed low pressure controls.
- Strong, attractive cabinet—louvered design protects the coil from damage
- Expansion Valves with Internal Check Valve—provides for quieter refrigerant metering
- Demand Defrost Control
- Non-Cycling Reversing Valve
- Hot Gas Muffler
- Service Valves
- Grille/motor mount for quiet fan operation
- Easily accessible control box
- Bi-Directional Filter Drier (shipped – not installed)
- Certified and rated under ARI Standard 240
- U.L. listed

GENERAL TERMS OF LIMITED WARRANTY

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable periods stated, in accordance with the terms of the limited warranty.

Conditional Parts Warranty*
(Registration Required)Ten (10) Years
Conditional Compressor*
(Registration Required)Ten (10) Years
Limited PartsFive (5) Years
*See Product Warranty Card for Details.

<u>13</u>	<u>P</u>	<u>J</u>	<u>L</u>	<u>18</u>	<u>A</u>	<u>01</u>
13 SEER	P = HEAT PUMP	VOLTAGE J = 208-230 SINGLE PHASE	DESIGN SERIES L = R-410A	NOMINAL COOLING CAPACITY	CABINET A = FULL METAL JACKET	RHEEM VALUE SERIES
				18 = 18,000 BTU/HR [5.28 kW] 24 = 24,000 BTU/HR [7.03 kW] 30 = 30,000 BTU/HR [8.79 kW] 36 = 36,000 BTU/HR [10.55 kW] 42 = 42,000 BTU/HR [12.31 kW] 48 = 48,000 BTU/HR [14.07 kW] 60 = 60,000 BTU/HR [17.58 kW]		

Price	Starting at: \$
-------	--------------------

