



# SALES FACT SHEET

**14AJM- SERIES**  
**Efficiencies up to 16 SEER/13 EER**  
**Nominal Sizes 1 1/2-5 Ton**  
**[5.28 to 17.6 kW]**  
**Cooling Capacities 17.3 to 60.5 kBTU**  
**[5.7 to 17.7 kW]**

## Rheem *Value Series*™ Air Conditioners



### Features:

- Outdoor air conditioner designed for ground level or rooftop installations. These units offer comfort and dependability for single, multi-family and light commercial applications.
- Painted louvered steel cabinet
- Easily accessible control box
- Condenser coils constructed with copper tubing and enhanced aluminum fins
- Grille/Motor mount for quiet fan operation
- Filter Drier (shipped – not installed)

### GENERAL TERMS OF LIMITED WARRANTY\*


Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Conditional Parts  
 (Registration Required) .....Ten (10) Years

\*For complete details of the Limited and Conditional Warranties, including applicable terms and conditions, contact your local contractor or the Manufacturer for a copy of the product warranty certificate.

Model 14AJM	Nominal Cooling Capacity	Voltage	Phase	Width "W" Inches [mm]	Length "L" Inches [mm]	Height "H" Inches [mm]	Service Valve - Liquid	Service Valve - Suction	Shipping Lbs. [kg]
19	18,000	208/230	1	27 <sup>5</sup> / <sub>8</sub> [702]	27 <sup>5</sup> / <sub>8</sub> [702]	24 <sup>1</sup> / <sub>4</sub> [616]	3/8"	3/4"	157 [71.2]
25	24,000	208/230	1	27 <sup>5</sup> / <sub>8</sub> [702]	27 <sup>5</sup> / <sub>8</sub> [702]	24 <sup>1</sup> / <sub>4</sub> [616]	3/8"	3/4"	171 [77.6]
30	30,000	208/230	1	31 <sup>5</sup> / <sub>8</sub> [803]	31 <sup>5</sup> / <sub>8</sub> [803]	27 <sup>3</sup> / <sub>8</sub> [695]	3/8"	3/4"	175 [79.4]
36	36,000	208/230	1	31 <sup>5</sup> / <sub>8</sub> [803]	31 <sup>5</sup> / <sub>8</sub> [803]	35 <sup>3</sup> / <sub>8</sub> [899]	3/8"	3/4"	201 [91.2]
42	42,000	208/230	1	31 <sup>5</sup> / <sub>8</sub> [803]	31 <sup>5</sup> / <sub>8</sub> [803]	35 <sup>3</sup> / <sub>8</sub> [899]	3/8"	3/4"	225 [102]
48	48,000	208/230	1	31 <sup>5</sup> / <sub>8</sub> [803]	31 <sup>5</sup> / <sub>8</sub> [803]	35 <sup>3</sup> / <sub>8</sub> [899]	3/8"	7/8"	269 [122]
49	47,000	208/230	1	31 <sup>5</sup> / <sub>8</sub> [803]	31 <sup>5</sup> / <sub>8</sub> [803]	35 <sup>3</sup> / <sub>8</sub> [899]	3/8"	7/8"	269 [122]
56	54,000	208/230	1	31 <sup>5</sup> / <sub>8</sub> [803]	31 <sup>5</sup> / <sub>8</sub> [803]	35 <sup>3</sup> / <sub>8</sub> [899]	3/8"	7/8"	274 [124.3]
60	60,000	208/230	1	31 <sup>5</sup> / <sub>8</sub> [803]	31 <sup>5</sup> / <sub>8</sub> [803]	35 <sup>3</sup> / <sub>8</sub> [899]	3/8"	7/8"	274 [124.3]

[ ] Designates Metric Conversions



"Proper sizing and installation of equipment is critical to achieve optimal performance. Ask your Contractor for details or visit [www.energystar.gov](http://www.energystar.gov)."



# SALES FACT SHEET

## ACCESSORIES

Description	Part No.	Price
Low Ambient Control (RXAD-A08)	RXAD-A08	
Crankcase Heater for 1.5 - 3 ton Models	44-17402-44	
Crankcase Heater for 3.5 - 5 ton Models	44-101884-01	
Low Pressure Control	RXAC-A07	
High Pressure Control	RXAB-A07	

**Total Price** \$