



SALES FACT SHEET



Featuring
New Industry Standard
R-410A Refrigerant

R-410A



"Visit www.Rheem.com
for complete details."



15PJL SERIES

GENERAL TERMS OF LIMITED WARRANTY

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable periods stated, in accordance with the terms of the limited warranty.

Conditional Parts Warranty* (Registration Required)Ten (10) Years
Conditional Compressor* (Registration Required)Ten (10) Years
Limited PartsFive (5) Years

*See Product Warranty Card for Details.

Features

- 35" Maximum Unit Height.
- Coils constructed with copper tubing and enhanced aluminum fins.
- Strong, attractive cabinet—louvered design protects the coil from damage.
- Expansion Valves with Internal Check Valve—Provides for quieter refrigerant metering.
- Enhanced Demand Defrost Control
- Factory Installed Low Pressure Control
- Non-Cycling Reversing Valve
- Hot Gas Muffler
- Service Valves
- Grille/motor mount for quiet fan operation.
- Easily accessible control box.
- Bi-Directional Filter Drier (Field Installed)
- Certified and rated under A.H.R.I. Standard 240.
- U.L listed.

Accessories/Options

- Optional High Pressure Control (Model No. RXAB-A07)
- Heat Pump Thermostat Warning Light Kit (Model No. RXPX-D01)
- Low Ambient Control (Model No. RXAD-A08)
- Outdoor Thermostats (Model No. RXPT-A01, A02, A03 or A04)
- Heat Pump Monitor (Model No. RXPM-B01)
- Thermostats and Subbases (Available through the PROSTOCK® department)
- Compressor Time Delay Control (Model No. RXMD-B01)
- Blower Time Delay Control (Model No. RXMD-C04) RXMD-C04 is not required if the outdoor unit is matched with a Rheem Value Series furnace or air handler, or if the furnace or air handler used has a blower off time delay built-in.
- Sound Enclosure*
- Start Components*

*Available through the PROSTOCK® department.

15	P	J	L	18	A	01
15 SEER	P = HEAT PUMP	VOLTAGE J = 208-230 SINGLE PHASE	DESIGN SERIES L = 1ST DESIGN (R-410A)	NOMINAL COOLING CAPACITY 18 = 18,000 BTU/HR [5.28 kW] 24 = 24,000 BTU/HR [7.03 kW] 30 = 30,000 BTU/HR [8.79 kW] 36 = 36,000 BTU/HR [10.55 kW] 42 = 42,000 BTU/HR [12.31 kW] 48 = 48,000 BTU/HR [14.07 kW] 60 = 60,000 BTU/HR [17.58 kW]	CABINET A = FULL METAL JACKET	RHEEM VALUE SERIES
Price	Starting at: \$					



(IN CERTAIN MATCHED SYSTEMS)

