

# PERFORMANCE PLATINUM™



The new degree of comfort.™

## The energy efficient PERFORMANCE PLATINUM™ Powered Damper gas water heaters meet or exceed the latest ENERGY STAR® requirements

### Efficiency

- .65 - .69 UEF
- ENERGY STAR® rated

### Performance

- FHR: 71 - 87 gallons
- Recovery rate is up to 40.4 gallons at a 90° F rise, depending on model

### Electronic Diagnostic Valve

- Electronic gas control for improved monitoring and service



### Low Emissions

- Eco-friendly burner, low NOx design
- Meets 40 ng/J NOx requirements



- EcoNet™ enabled for integration with home automation, energy management and demand response systems



### Technology

- 24 VAC flue damper, 120 VAC outlet required
- Includes 19-foot cord, 3-prong plug
- Standard Cat. I, double-wall, B-vent, 3"/4" combo vent




### Maintenance Free Burner System

- Exclusive air/fuel shut-off device
- Maintenance free – no filter to clean
- Disables the heater in the presence of flammable vapor accumulation



Combustion Shut-off System



Flame Arrestor Plate

### Self-Cleaning

- Fights sediment and mineral build-up
- Reduces fuel costs



### Longer Life

- Premium grade anode rod provides long-lasting tank protection

### High Altitude Compliant

- Certified to 10,200 ft. above sea level

### Plus...

- Dual certified for both potable water and space heating
- Durable brass drain valve
- Temperature and pressure relief valve included
- Low lead compliant

### Warranty

- 12-Year limited warranty for tank and parts, 3-year full in-home labor warranty\*

\*See written warranty for complete details

Units meet or exceed ANSI requirements and have been tested according to D.O.E. procedures. Units meet or exceed the energy efficiency requirements of NAECA, ASHRAE standard 90, ICC Code and all state energy efficiency performance criteria.



## PERFORMANCE PLATINUM Powered Damper 38, 40 and 50-Gallon Capacities Up to 40,000 Btu/h



LEED Point = 1

### What is a Powered Damper?

The 24-volt powered flue damper is positioned atop the unit. It opens and closes automatically in response to gas-burner activity. When the combustion stops, it signals the damper to close, trapping the heat inside the flue and delivering more heat to the water.

See dimensions chart on back.



The new degree of comfort.™


# PERFORMANCE PLATINUM™ Powered Damper Specifications

Fuel Type	Description	Nominal Gallon Capacity	Rated Gallon Capacity	Model Number	Gas Input in Thous. Btu/h	Recovery in G.P.H. 90° F Rise	First Hour Delivery G.P.H.	Ht. to Vent A	Tank Height B	Diam. C	Ht. to Gas Conn. D	Vent Size E	Water Conn. Center F	Ht. to Side T&P Valve G	Water Conn. Size H	Ship Weight (LBS)	Energy Factor	Uniform Energy Factor (UEF)	
<b>Performance Platinum - ENERGY STAR® Powered Damper Gas Products with EcoNet WiFi Module Included</b>																			
Natural Gas	Tall	50	48	XG50T12DM40UOW	40	40.4	81	63-1/2	58-1/2	21-3/4	14	3 or 4	8	52-1/2	3/4	160	0.67	0.69	
Natural Gas	Tall	38	37	XG40T12DM40UOW	40	40.4	72	63	58	19-3/4	14	3 or 4	8	52-1/4	3/4	140	0.69	0.66	
Natural Gas	Short	40	38	XG40S12DM40UOW	40	40.4	71	55-1/2	50-1/2	21-3/4	14	3 or 4	8	44	3/4	140	0.67	0.65	
<b>Performance Platinum - ENERGY STAR® Powered Damper Gas Products</b>																			
Natural Gas	Tall	50	48	XG50T12DM40UO	40	40.4	87	63-1/2	58-1/2	21-3/4	14	3 or 4	8	52-1/2	3/4	160	0.67	0.69	
Natural Gas	Short	50	48	XG50S12DM40UO	40	40.4	86	55-1/2	50-1/2	23-3/4	14	3 or 4	8	44	3/4	160	0.67	0.69	
Natural Gas	Tall	38	37	XG40T12DM40UO	40	40.4	72	63	58	19-3/4	14	3 or 4	8	52-1/4	3/4	140	0.69	0.66	
Natural Gas	Short	40	38	XG40S12DM40UO	40	40.4	71	55-1/2	50-1/2	21-3/4	14	3 or 4	8	44	3/4	140	0.67	0.65	
Liquid Propane	Tall	50	48	XP50T12DM36UO	36	36.4	87	63-1/2	58-1/2	21-3/4	14	3 or 4	8	52-1/2	3/4	160	0.67	0.69	
Liquid Propane	Short	50	48	XP50S12DM36UO	36	36.4	86	55-1/2	50-1/2	23-3/4	14	3 or 4	8	44	3/4	160	0.67	0.69	
Liquid Propane	Tall	38	37	XP40T12DM36UO	36	36.4	72	63	58	19-3/4	14	3 or 4	8	52-1/4	3/4	140	0.69	0.66	
Liquid Propane	Short	40	38	XP40S12DM36UO	36	36.4	71	55-1/2	50-1/2	21-3/4	14	3 or 4	8	44	3/4	140	0.67	0.65	

Uniform Energy Factor, Energy Factor and rated gallon capacity based on Department of Energy (DOE) requirements.



LEED Point = 1



*In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice.*

Rheem Water Heating • 101 Bell Road  
Montgomery, Alabama 36117-4305 • www.rheem.com