SALES FACT SHEET

Equipped with the *Comfort Control System*™

- Increased Reliability
- On-Board Diagnostics
- Fault Recall
- *Active Protection*™

Rheem Prestige® SERIES

RANL- JEZ SERIES

R-410A earth friendly refrigerant

Six Models

Efficiencies ranging up to 15.00 SEER in certain matched systems.
Nominal Sizes 2 to 5 Tons
[7 kW] to [17.58 kW]

GENERAL TERMS OF LIMITED WARRANTY

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Condenser Coil leaks caused by factory defects . . . . . .Five (5) Years
Compressor . . . . . .Ten (10) Years
*Any Other Part . . . . . .Five (5) Years

RANL- JEZ Series Conditional Replacement Warranty:
Rheem will provide a replacement model (if an exact replacement is not available, an equivalent product will be provided) to the original purchaser if the compressor fails within 5 years (providing the unit is installed with a new Rheem Air Handler OR Rheem Indoor Coil with a Rheem Gas Furnace, and is properly matched as specified by Rheem and/or listed in the Air Conditioning Institute (ARI) published rating, and if additional conditions are satisfied. See product warranty card for additional information.

***This five year limited warranty is applicable only to single-phase products installed in residential applications on or after January 1, 2001.**

Features

The Rheem *Prestige Series*® RANL- JEZ Condensing Unit was designed with performance in mind. These units offer comfort, energy conservation and dependability for single, multi-family and light commercial applications.

- The *Comfort Control System*™ provides on-board diagnostics and fault history for condensing units with single-phase compressors by detecting system and electrical problems without adding sensors. It can also communicate "fault codes" to enabled "L terminal" thermostats. The integrated diagnostics with *Active Protection* prevents compressor operation when damage would occur.
- 7-Segment LED Display is exclusive only to Rheem products. The information-display quickly and accurately shows technicians the source of malfunctions.
- Five-year conditional unit replacement warranty.
- Compressor sound blanket is standard to provide quiet operation.
- Attractive, louvered wrap-around jacket protects the coil from yard hazards and weather extremes. Top grille is steel reinforced for extra strength. Cabinet is powder painted for all-weather protection.
- Air is discharged upward away from bushes and shrubs. The discharge pattern of the top grille provides minimum air restriction.
- Combination Grille/Motor Mount secures the motor to the underside of the discharge grille. The grille protects the motor windings and bearings from rain and snow.
- Removable top grille provides access to the condenser fan motor and condenser coil.
- Single speed 8-pole fan motor designed for low speed, quiet, energy-saving operation.
- All models meet or exceed a 1000-hour salt spray test per ASTM B117 Standard Practice for Operating Salt Spray Testing Apparatus.

R	A	N	L	—	024	J	E	Z
RHEEM	REMOTE CONDENSING UNIT	13 SEER	DESIGN SERIES L = R-410A		COOLING CAPACITY 024 = 24,000 BTU/HR [7.03 kW] 030 = 30,000 BTU/HR [8.79 kW] 036 = 36,000 BTU/HR [10.55 kW] 042 = 42,000 BTU/HR [12.31 kW] 048 = 48,000 BTU/HR [14.07 kW] 060 = 60,000 BTU/HR [17.58 kW]	ELECTRICAL DESIGNATION J = 208/230V-1-60	VARIATIONS EQUIPPED WITH THE *COMFORT CONTROL SYSTEM*™	COOLING CONNECTION FITTING Z = SWEAT W/SCROLL

Price	Starting at: $

Accredited by the RvA — ABS Quality Evaluations, Inc. Management System Certification — ANAB ACCREDITED
ISO 9001:2000
Certificate Number: 30164

ENERGY STAR PARTNER
(IN CERTAIN MATCHED SYSTEMS)

ENERGUIDE — Seasonal Energy Efficiency Ratio (SEER) — THIS MODEL 13.0 — 13.0 — Uses least energy → 21.0

ARI PERFORMANCE CERTIFIED™
ARI Standard 210/240 UAC

c UL® us LISTED