



SALES FACT SHEET



CLASSIC® SERIES SUPER QUIET 80™ 80% A.F.U.E. UPFLOW/HORIZONTAL GAS FURNACES w/ECM MOTOR

Features

- ECM X-13 Motor for reduced power consumption and improved A/C efficiency.
- Innovative combustion design results in reliable, efficient operation at sound levels which provide distinct competitive advantage.
- Patented Heat Exchanger, constructed of both stainless and aluminized steel for the maximum in corrosion resistance.
- Low profile "34 inch" design is lighter and easier to handle, and leaves room for optional equipment.
- Convertible from upflow to horizontal left or right without field conversion.
- Left or right side gas and electric inlet connections with quick, simple change.
- Robust and reliable direct spark ignition utilizing remote sense and an integrated board with humidifier and electronic air cleaner hookups.
- Insulated blower compartment helps to reduce jacket loss and noise.
- Pre-paint galvanized steel cabinet.
- Molded permanent filter.
- Grab-holes in doors to aid in easy door removal and replacement.

A variety of cooling coils and plenums designed to use with Rheem *Classic® Series Super Quiet 80™* gas furnaces are available as optional accessories. These furnaces can be installed in an upflow position or laid on either side in a horizontal position. Field conversion not required.

GENERAL TERMS OF LIMITED WARRANTY

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Gas Heat Exchanger Limited WarrantyTwenty (20) Years
Conditional Parts Warranty* (Registration Required)Ten (10) Years

*Refer to Product Warranty Card for Details.

RGPT- SERIES ECM Equipped Models with Input Rates from 50,000 to 125,000 BTU/HR [15 to 37 kW]

(U.S. & Canadian Models)

MODEL	INPUT- BTU/HR [kW] ①	HEATING CAPACITY BTU/HR [kW] ②	HEATING CFM @ .5" [.12 kPa] W.C. E.S.P. [L/s]	COOLING CFM @ .5" [.12 kPa] W.C. E.S.P. [L/s]	APPROX. SHIPPING WEIGHT (LBS.) [kg]	PRICE
RGPT-05*BMKR	50,000 [15]	41,000 [12]	823 [388]	1600 [755]	105 [48]	
RGPT-07*AMKR	75,000 [22]	60,000 [18]	1053 [497]	1200 [566]	105 [48]	
RGPT-07*BRQR	75,000 [22]	60,000 [18]	1211 [572]	2000 [944]	120 [54]	
RGPT-10*BRMR	100,000 [29]	81,000 [24]	1445 [682]	2000 [944]	120 [54]	
RGPT-12*ARRM	125,000 [37]	99,000 [29]	1730 [816]	2000 [944]	140 [63]	

① In accordance with D.O.E. test procedures. ② See Conversion Kit Index Form for high altitude derate.
*E=Standard, N=NO_x Models

[] Designates Metric Conversions

