



SALES FACT SHEET



GENERAL TERMS OF LIMITED WARRANTY

Rheem® will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Indoor Coils leaks caused by factory defectsFive (5) Years
Electric Heating ElementFive (5) Years
Any Other PartFive (5) Years

For Complete Details of the Limited Warranty, including Applicable Terms & Conditions, See Your Local Installer or Contact the Manufacturer for a Copy.

RBHP- AIR HANDLERS

- Models featuring R-22 Refrigerant
- Models featuring Earth-Friendly R-410A Refrigerant 
- Models featuring Electric Heat without Indoor Cooling Coil

Features

- Quiet and efficient X-13 motor technology
- Only 35" tall and 4-way convertible for all those tight spaces
- Available from factory in upflow and horizontal configurations
- Nominal airflow up to 0.5" external static pressure with reduced airflow up to 1.0" external static pressure
- Factory installed MultiFlex® coils
- Sturdy double wall construction with .5 inch [12.7 mm] of foil faced insulation for excellent sound and insulating characteristics
- Permanent, easily accessible and washable filter furnished standard
- Circuit breaker (standard on units with more than 11 kW) meets U.L. and cUL requirements for service disconnect
- Factory installed auxiliary electric heat provides exact heat for indoor comfort over a variety of applications
- Watt restrictors, standard on RBHP-17 models above 6 kW and on RBHP-21, RBHP-24 and RBHP-25 models above 11 kW, stage supplemental heat so that only the necessary amount is engaged to maintain comfort in the conditioned space
- Fan settings for selectable, customized cooling airflow over a wide variety of applications

Rheem **Classification**
B = Blower Unit
Application
H = Heat Pump Air Handler
Design Series
P = X-13 Motor
Cabinet Size
17 = 17.5" [431.8 mm]
21 = 21.0" [533.4 mm]
24 = 24.5" [609.6 mm]
25 = 24.5" [635 mm]

Coil Code
A = No Coil

Coil Code	Refrigerant Type	Cabinet Width			
		17	21	24	25
D	R-22	RCHJ-24A1GH17	RCHJ-36A1GH21	RCHJ-48A1GH24	
E	R-22				RCHJ-60A1GH24
1	R-410A	RCHL-24A2GH17			
2	R-410A		RCHL-36A1GH21		
4	R-410A			RCHL-48A1GH24	
7	R-410A				RCHL-60A1GH24

Airflow
Horizontal Multi-Position

Control
N = No Circuit Protection (Single Circuit)
S = Circuit Breaker (Single Circuit)

Electric Heat
00 = No Heat
06 = 4.9 kW
07 = 7.0 kW
11 = 10.0 kW
14 = 14.0 kW
18 = 17.5 kW
21 = 21.0 kW

Voltage
A = 115V-1-60
J = 208/240V-1-60

Available Models featuring R-22 Refrigerant

RBHP-17A00NHD
RBHP-17J06SHD
RBHP-17J07SHD
RBHP-17J17SHD
RBHP-21A00NHD
RBHP-21J06SHD
RBHP-21J07SHD
RBHP-21J11SHD
RBHP-21J14SHD
RBHP-24A00NHD
RBHP-24J06SHD
RBHP-24J07SHD
RBHP-24J11SHD
RBHP-24J14SHD
RBHP-24J18SHD
RBHP-25A00NHE
RBHP-25J11SHE
RBHP-25J14SHE
RBHP-25J18SHE
RBHP-25J21SHE

Available Models featuring R-410A Refrigerant

RBHP-17A00NH1
RBHP-17J06SH1
RBHP-17J07SH1
RBHP-17J11SH1
RBHP-21A00NH2
RBHP-21J06SH2
RBHP-21J07SH2
RBHP-21J11SH2
RBHP-21J14SH2
RBHP-24A00NH4
RBHP-24J06SH4
RBHP-24J07SH4
RBHP-24J11SH4
RBHP-24J14SH4
RBHP-24J18SH4
RBHP-25A00NH7
RBHP-25J11SH7
RBHP-25J14SH7
RBHP-25J18SH7
RBHP-25J21SH7

Available Models (without coils)

RBHP-17J11SHA
RBHP-21J14SHA
RBHP-24J18SHA
RBHP-25J21SHA

Price

Starting at:
\$

