Rneem SALES FACT SHEET

R801T- SERIES

80% A.F.U.E.† Models with Input Rates of 75 to 125 kBTU [22 to 37 kW]



GENERAL TERMS OF LIMITED WARRANTY*

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty. Heat ExchangerTwenty (20) Years

Conditional Parts (Registration Required)Ten (10) Years

+ A ELLE (Appuel Evel Liferation Efficiency) calculated in accordance with

+A.F.U.E. (Annual Fuel Utilization Efficiency) calculated in accordance with Department of Energy test procedures.

*For complete details of the Limited and Conditional Warranties, including applicable terms and conditions, contact your local contractor or the Manufacturer for a copy of the product warranty certificate.

| MODEL | INPUT- BTU/HR [kW] | HEATING CAPACITY BTU/HR [kW] | HEATING CFM @ .2" [.049 kPa] W.C. E.S.P. [L/s] | COOLING CFM @ .5" [.124 kPa] W.C. E.S.P. [L/s] | APPROX. SHIPPING WEIGHT (LBS.) [kg] | PRICE |
|-----------------|-----------------------|---------------------------------|--|--|--|-------|
| R801TA075317Z*A | 75,000 [22] | 60,000 [18] | 1333 [629] | 1200 [566] | 105 [48] | |
| R801TA075521Z*A | 75,000 [22] | 60,000 [18] | 1564 [738] | 2000 [944] | 120 [54] | |
| R801TA100521Z*A | 100,000 [29] | 81,000 [24] | 1877 [886] | 2000 [944] | 120 [54] | |
| R801TA125524Z*A | 125,000 [37] | 99,000 [29] | 1859 [877] | 2000 [944] | 140 [63] | |

[] Designates Metric Conversions



Rheem Heating, Cooling and Water Heating P.O. Box 17010, Fort Smith, AR 72917

Rheem *Classic Plus*[™] Series Downflow Gas Furnace

Features

- 80% residential Gas Furnace CSA certified
- PlusOne[™] Diagnostics 7 Segment LED all units
- PlusOne[™] Ignition System DSI for reliability and longevity
- Heat exchanger is removable for improved serviceability. Aluminized steel construction provides maximum corrosion resistance and thermal fatigue reliability.
- Low profile 34" cabinet ideal for space constrained installations
- Integrated Control board features dip switches for easy system set up
- QR code for quick access to product information from your smart phone or tablet
- Insulated blower compartment
- Constant Torque electrically commutated motor



Rheem SALES FACT SHEET

R801T DOWNFLOW

| Description | Part No. | Price |
|--|----------|-------|
| Filter Rack | RXGF-CC | |
| Combustible Floor Base for R801T075317 | RXGC-B17 | |
| Combustible Floor Base for R801TA100521, R801T075521 | RXGC-B21 | |
| Combustible Floor Base for R801T125 | RXGC-B24 | |