

NEXT-GEN ALL-TEMP

LOW PROFILE UNIT COOLER

AIR, ELECTRIC & HOT GAS DEFROST MODELS

2,700 to 45,900 BTUH

**SMALL TO MEDIUM WALK-INS
COOLER & FREEZER APPLICATIONS**



NEXT-GEN ALL-TEMP

Features

Kramer Low Profile Unit Coolers feature an air draw-through design and are available in air, electric and hot gas defrost configurations. We've taken these all-purpose unit coolers to the next level with the release of the Next-Gen All-Temp models. The units feature a new fan guard design and deep draw venturi to achieve optimal airflow, easy access for serviceability, and can be used with multiple refrigerants.

SIZES

There are a wide array of sizes available with capacities ranging from 2,700 to 45,900 BTUH at a 10°TD. One through six fan models are available with air flow spanning a range of 800 to 4,650 CFM.

HOUSING

The embossed aluminum casing is lightweight yet durable. Each fan section is baffled to prevent short cycling of the discharge air. The units are designed to mount flush to the ceiling and are compliant with NSF requirements. The top pan includes 1/2" wide slotted mounting points to simplify installation. The removable drain fitting is installed into the bottom of the drain pan for easy field connection and it can be quickly replaced without changing out the entire drain pan. End panels can be slid out from the front of the unit providing easy serviceability from the front or side of the unit, allowing convenient access to the roomy electrical and piping compartments.

COIL

Copper hairpins consist of high efficiency 3/8" enhanced copper tubes which are staggered and mechanically expanded into corrugated aluminum fins achieving maximum heat transfer while reducing refrigerant charge. Die formed fin collars provide even fin spacing. Models are available in 4 and 6 fins per inch. Sweat connections are standard on all models.

MOTORS

Standard models feature highly efficient Electronically Commutated (EC) motors that can be field or factory wired for dual speed operation. Dual Speed EC motors are available for 115V or 208/230V and are compliant with California Title 24 regulations. PSC motors are also available for 115V, 208/230V or 460V requirements. All motors include thermal overload protection.

CONFIGURATIONS

Units are available as fully configurable (no mounted accessories) or they can be pre-assembled with the most requested options pre-installed at the factory.

Pre-assembly Code¹:

- Blank = Configurable (no factory installed options)
- T = Factory mounted mechanical TXV
- L = Factory mounted mechanical TXV, Liquid Line Solenoid and mechanical T-Stat
- M = Master Configuration with mounted mechanical TXV, mechanical T-Stat, LLS and copper Tee

FANS

Heavy duty 12" aluminum fans are balanced to provide vibration-free operation. New and improved black plastic fan guard design and deep draw venturi provide an optimal air pattern.

ELECTRICAL

Available for 115V, 115-230V (Air Defrost EC motor only), 208/230V and 460V (see pages 5 through 9). A large electrical compartment is supplied internal to the unit to house the electrical components and is easily accessible by removing the slide out end panel. All models are UL and cUL listed and are available for 60 Hz or 50 Hz applications.

AIR DEFROST

Air Defrost models (KL6A) are designed for use in coolers 35°F and warmer. All components are factory wired to convenient screw-type terminal strips.

ELECTRIC DEFROST

Electric Defrost models (KL*E) are designed for use in coolers and freezers between 34°F to -20°F. Defrost heaters are mounted on the air intake side of the unit for optimal performance and easy maintenance. A lower heater is installed inside the drain pan for fast, reliable drainage. A defrost termination fan delay thermostat (DTFD) terminates the defrost cycle when the temperature is satisfied. The fan delay allows the warm coil to cool after a defrost cycle prior to the fans turning on. A heater safety thermostat is installed to prevent overheating.

HOT GAS DEFROST

There are two types of Hot Gas Defrost models available: 3-pipe Hot Gas models (KL*H) and 2-pipe Hot Gas Reverse Cycle units (KL*G) (see pages 10 through 11 for more details). Hot Gas Defrost models are designed for use in coolers and freezers between 34°F and -20°F. All Hot Gas units include a fixed DTFD factory wired and an electric drain pan heater.

Optional Features

- Coated fin pack² (Baked epoxy, ElectroFin³, Bronz-Glow, or Heresite)
- Coated housing³ (same coatings as above)
- Adjustable termination/ fan delay control⁴
- Insulated drain pan⁴

Notes

* Asterisk represents a variable character based on fins per inch. See page 4 for nomenclature.

1. Codes T, L and M are intended for units in finished goods inventory only. Call out each required option separately for units ordered for normal lead time delivery.
2. Option available for all models.
3. ElectroFin coating is not NSF approved. NSF approval label will be removed from unit if ordered with this coating.
4. Option available for electric and hot gas defrost models.

Highlighted Features and Options



FANS

- 12" heavy duty aluminum fans are balanced for vibration-free operation
- High efficiency fan guard design and deep draw venturi provide optimal air flow



HOUSING

- Lightweight and durable embossed aluminum casing
- Mounts flush to ceiling to maximize storage space
- Slide out end panels
- NSF approved

ELECTRICAL AND PIPING



Unit shown
with optional
components
installed

- End panels slide out for easy service from the front or sides of the unit
- Ample room in electrical and piping compartments for easy access



COILS AND DEFROST HEATERS

- Available in 4 or 6 fins per inch (FPI)
- Electric defrost heaters are mounted on the air intake coil face to provide optimal performance and easy service access
- The drain pan heater is affixed to the drain pan and is easily removable for service or cleaning

NEXT-GEN ALL-TEMP

Electronically commutated motors bring energy efficiency to the refrigeration Unit Cooler market. Features of the EC motors we offer include:

- Integrated control with sealed construction
- Locked rotor and overload protection
- Durable ball bearing construction for long commercial life
- Unique Hall Effect Sensor design prevents syncing or resonance
- Threaded shaft uses hubless fan blade
- Motors can be configured for single or dual speed operation
- Dual voltage motor internal power supply operates at correct rpm from 115-230 VAC



Energy Savings by Switching from PSC to Efficient EC Motor

Chart is based on Energy Cost of \$0.10 per kWh.

Motor Change	Std Motor Power Watts/Mtr	Change to Motor Power Watts/Mtr	Reduced Power Watts/Mtr	Run Time Hrs/Day	Motor Energy Savings kWh/Yr	Motor Energy Savings \$/Yr	Reduced Box Load MBTU/Yr	Cond. Unit Energy Savings \$/Yr	Yearly Saving \$ Per MTR	Pay back in Yrs
PSC to EC	85	47	38	22	305	31	1041	20	51	2.0

PSC = 1/20 HP PSC motor

EC = 50 Watt Electronically Commutated motor



Performance and Electrical Data - Air Defrost Models - 6 FPI

Model Number	BTUH Capacity @ 25°F S.T. & 10°F TD		CFM	No. of Fans	Total Fan Motor AMPS - 1 Phase					MCA	MOPD				
					EC Motors [†]		PSC Motors								
	R404A/ CO ₂ DX	R407A/ R448A/ R449A/B [▲]			115V	208- 230V	115V	208- 230V	460V						
KL6A041***	4,100	4,800	800	1	0.8	0.5	1.0	0.5	0.4						
KL6A052***	5,200	6,000	785	1	0.8	0.5	1.0	0.5	0.4	15.0	20				
KL6A066***	6,600	7,800	775	1	0.8	0.5	1.0	0.5	0.4						
KL6A073***	7,300	8,500	1,600	2	1.6	1.0	2.0	1.0	0.8						
KL6A094***	9,400	10,900	1,570	2	1.6	1.0	2.0	1.0	0.8	15.0	20				
KL6A117***	11,700	13,600	1,550	2	1.6	1.0	2.0	1.0	0.8						
KL6A130***	13,000	15,300	1,550	2	1.6	1.0	2.0	1.0	0.8						
KL6A141***	14,100	16,300	2,355	3	2.4	1.5	3.0	1.5	1.2	15.0	20				
KL6A161***	16,100	18,800	2,355	3	2.4	1.5	3.0	1.5	1.2						
KL6A181***	18,100	21,200	2,325	3	2.4	1.5	3.0	1.5	1.2						
KL6A195***	19,500	22,500	3,140	4	3.2	2.0	4.0	2.0	1.6	15.0	20				
KL6A235***	23,500	27,800	3,140	4	3.2	2.0	4.0	2.0	1.6						
KL6A260***	26,000	30,400	3,100	4	3.2	2.0	4.0	2.0	1.6						
KL6A295***	29,500	36,100	3,875	5	4.0	2.5	5.0	2.5	2.0	15.0	20				
KL6A330***	33,000	38,800	4,650	6	4.8	3.0	6.0	3.0	2.4						
KL6A390***	39,000	45,900	4,650	6	4.8	3.0	6.0	3.0	2.4						

Use EC motors for 50 Hz operation.

* Each asterisk represents a variable character based on voltage, motor and vintage ordered. See page 4 for nomenclature.

^ Refrigerants with large glides are rated at dew point temperature. Use R407A capacity ratings for R407C and R407F.

† These Electronically Commutated (EC) Motors are not available for 460V. EC Motors can be field or factory wired for dual-speed operation. Dual-speed EC motors are compliant with California Title 24 regulations.

Energy Independence and Security Act of 2007 specifies that walk-in coolers and freezers under 3,000 square feet that are manufactured after January 1, 2009 shall have evaporators with EC motors when they are single phase, less than 460 volt and less than 1 HP.

Mounts flush to the ceiling to maximize storage space

UL certified for use with multiple refrigerants

Single fan through six fan models are available



Performance and Electrical Data - Electric Defrost Models - 6 FPI

Model Number	BTUH Capacity @ -20°F S.T. & 10°F TD ¹		CFM	No. of Fans	Total Fan Motor AMPS - 1 Phase			MCA	MOPD
					EC Motors [†]	PSC Motors			
	R404A / CO ₂ DX	R407A/ R448A/ R449A/B ^A			230V	230V	460V		
KL6E035***	3,500	4,000	800	1	0.5	0.5	0.4		
KL6E042***	4,200	4,900	785	1	0.5	0.5	0.4	15.0	20
KL6E049***	4,900	5,600	775	1	0.5	0.5	0.4		
KL6E066***	6,600	7,600	1,600	2	1.0	1.0	0.8		
KL6E077***	7,700	8,800	1,570	2	1.0	1.0	0.8	15.0	20
KL6E090***	9,000	10,600	1,550	2	1.0	1.0	0.8		
KL6E105***	10,500	12,400	1,550	2	1.0	1.0	0.8		
KL6E121***	12,100	14,200	2,355	3	1.5	1.5	1.2	15.0	20
KL6E142***	14,200	16,600	2,325	3	1.5	1.5	1.2		
KL6E162***	16,200	18,700	3,140	4	2.0	2.0	1.6		
KL6E182***	18,200	21,000	3,100	4	2.0	2.0	1.6	15.0	20
KL6E200***	20,000	22,800	3,925	5	2.5	2.5	2.0		
KL6E244***	24,400	27,900	4,710	6	3.0	3.0	2.4	15.0	20
KL6E281***	28,100	33,000	4,650	6	3.0	3.0	2.4		

Model Number	Heater Amps			Heater Watts
	230V		460V	
	1PH	3PH	1PH	
KL6E035***	4.9	—	2.5	1,125
KL6E042***	4.9	—	2.5	1,125
KL6E049***	4.9	—	2.5	1,125
KL6E066***	9.8	—	4.9	2,250
KL6E077***	9.8	—	4.9	2,250
KL6E090***	9.8	—	4.9	2,250
KL6E105***	9.8	—	4.9	2,250
KL6E121***	14.3	—	7.2	3,300
KL6E142***	14.3	—	7.2	3,300
KL6E162***	19.2	—	9.6	4,425
KL6E182***	19.2	—	9.6	4,425
KL6E200***	24.1	14.0	12.0	5,550
KL6E244***	29.0	16.8	14.5	6,675
KL6E281***	29.0	16.8	14.5	6,675

¹ Capacity Correction for Electric and Hot Gas Defrost Evaporators						
S.S.T. (dew)	20°F	0°F	-10°F	-20°F	-30°F	
Multiply Capacity by:	1.15	1.075	1.0375	1	0.9625	

Use EC motors for 50 Hz operation.

— Not available.

* Each asterisk represents a variable character based on voltage, motor and vintage ordered. See page 4 for nomenclature.

^ Refrigerants with large glides are rated at dew point temperature. Use R407A capacity ratings for R407C and R407F.

† These Electronically Commutated (EC) Motors are not available for 460V. EC Motors can be field or factory wired for dual-speed operation. Dual-speed EC motors are compliant with California Title 24 regulations.

Energy Independence and Security Act of 2007 specifies that walk-in coolers and freezers under 3,000 square feet that are manufactured after January 1, 2009 shall have evaporators with EC motors when they are single phase, less than 460 volt and less than 1 HP.

Performance and Electrical Data - Electric Defrost - 4 FPI

Model Number	BTUH Capacity @ -20°F S.T. & 10°F TD ¹		CFM	No. of Fans	Total Fan Motor AMPS - 1 Phase			MCA	MOPD
					EC Motors [†]	PSC Motors			
	R404A / CO ₂ DX	R407A/ R448A/ R449A/B [▲]			230V	230V	460V		
KL4E027***	2,700	3,100	800	1	0.5	0.5	0.4		
KL4E032***	3,200	3,800	785	1	0.5	0.5	0.4	15.0	20
KL4E038***	3,800	4,400	775	1	0.5	0.5	0.4		
KL4E051***	5,100	5,900	1,600	2	1.0	1.0	0.8		
KL4E064***	6,400	7,300	1,570	2	1.0	1.0	0.8	15.0	20
KL4E080***	8,000	9,500	1,550	2	1.0	1.0	0.8		
KL4E094***	9,400	11,000	2,355	3	1.5	1.5	1.2		
KL4E110***	11,000	12,800	2,325	3	1.5	1.5	1.2	15.0	20
KL4E125***	12,500	14,400	3,140	4	2.0	2.0	1.6		
KL4E141***	14,100	16,300	3,100	4	2.0	2.0	1.6		
KL4E155***	15,500	17,700	3,925	5	2.5	2.5	2.0	15.0	20
KL4E195***	19,500	22,300	4,710	6	3.0	3.0	2.4		
KL4E230***	23,000	27,000	4,650	6	3.0	3.0	2.4		

Model Number	Heater Amps			Heater Watts
	230V		460V	
	1PH	3PH	1PH	
KL4E027***	4.9	–	2.5	1,125
KL4E032***	4.9	–	2.5	1,125
KL4E038***	4.9	–	2.5	1,125
KL4E051***	9.8	–	4.9	2,250
KL4E064***	9.8	–	4.9	2,250
KL4E080***	9.8	–	4.9	2,250
KL4E094***	14.3	–	7.2	3,300
KL4E110***	14.3	–	7.2	3,300
KL4E125***	19.2	–	9.6	4,425
KL4E141***	19.2	–	9.6	4,425
KL4E155***	24.1	14.0	12.0	5,550
KL4E195***	29.0	16.8	14.5	6,675
KL4E230***	29.0	16.8	14.5	6,675

¹ Capacity Correction for Electric and Hot Gas Defrost Evaporators					
S.S.T. (dew)	20°F	0°F	-10°F	-20°F	-30°F
Multiply Capacity by:	1.15	1.075	1.0375	1	0.9625

Use EC motors for 50 Hz operation.

– Not available.

* Each asterisk represents a variable character based on voltage, motor and vintage ordered. See page 4 for nomenclature.

▲ Refrigerants with large glides are rated at dew point temperature. Use R407A capacity ratings for R407C and R407F.

† These Electronically Commutated (EC) Motors are not available for 460V. EC Motors can be field or factory wired for dual-speed operation. Dual-speed EC motors are compliant with California Title 24 regulations.

Energy Independence and Security Act of 2007 specifies that walk-in coolers and freezers under 3,000 square feet that are manufactured after January 1, 2009 shall have evaporators with EC motors when they are single phase, less than 460 volt and less than 1 HP.

Electric Defrost Kits

MODEL NUMBER	1 UNIT COOLER PER SYSTEM			2 UNIT COOLERS PER SYSTEM			3 UNIT COOLERS PER SYSTEM		
	230V/1	230V/3	460V/1	230V/1	230V/3	460V/1	230V/1	230V/3	460V/1

6 FPI

KL6E035***	ED5-A2	-	ED17-A4	ED20-A2*	-	ED22-A4	ED30-A2	-	ED32-A4
KL6E042***	ED5-A2	-	ED17-A4	ED20-A2*	-	ED22-A4	ED30-A2	-	ED32-A4
KL6E049***	ED5-A2	-	ED17-A4	ED20-A2*	-	ED22-A4	ED30-A2	-	ED32-A4
KL6E066***	ED5-A2	-	ED17-A4	ED20-A2*	-	ED22-A4	ED30-A2	-	ED32-A4
KL6E077***	ED5-A2	-	ED17-A4	ED20-A2*	-	ED22-A4	ED30-A2	-	ED32-A4
KL6E090***	ED5-A2	-	ED17-A4	ED20-A2*	-	ED22-A4	ED30-A2	-	ED32-A4
KL6E105***	ED5-A2	-	ED17-A4	ED20-A2*	-	ED22-A4	ED33-A2	-	ED32-A4
KL6E121***	ED5-A2	-	ED17-A4	ED20-A2*	-	ED22-A4	ED33-A2	-	ED32-A4
KL6E142***	ED5-A2	-	ED17-A4	ED20-A2*	-	ED22-A4	ED33-A2	-	ED32-A4
KL6E162***	ED6-A2	-	ED17-A4	ED23-A2*	-	ED22-A4	ED35-A2	-	ED32-A4
KL6E182***	ED6-A2	-	ED17-A4	ED23-A2*	-	ED22-A4	ED35-A2	-	ED32-A4
KL6E200***	ED7-A2	ED11-B2	ED17-A4	ED23-A2*	ED21-B2*	ED22-A4	ED35-A2	ED33-B2	ED34-A4
KL6E244***	ED7-A2	ED11-B2	ED17-A4	ED25-A2*	ED23-B2*	ED22-A4	ED35-A2	ED35-B2	ED34-A4
KL6E281***	ED7-A2	ED11-B2	ED17-A4	ED25-A2*	ED23-B2*	ED22-A4	ED35-A2	ED35-B2	ED34-A4

4 FPI

KL4E027***	ED5-A2	-	ED17-A4	ED20-A2*	-	ED22-A4	ED30-A2	-	ED32-A4
KL4E032***	ED5-A2	-	ED17-A4	ED20-A2*	-	ED22-A4	ED30-A2	-	ED32-A4
KL4E038***	ED5-A2	-	ED17-A4	ED20-A2*	-	ED22-A4	ED30-A2	-	ED32-A4
KL4E051***	ED5-A2	-	ED17-A4	ED20-A2*	-	ED22-A4	ED30-A2	-	ED32-A4
KL4E064***	ED5-A2	-	ED17-A4	ED20-A2*	-	ED22-A4	ED30-A2	-	ED32-A4
KL4E080***	ED5-A2	-	ED17-A4	ED20-A2*	-	ED22-A4	ED30-A2	-	ED32-A4
KL4E094***	ED5-A2	-	ED17-A4	ED20-A2*	-	ED22-A4	ED30-A2	-	ED32-A4
KL4E110***	ED5-A2	-	ED17-A4	ED20-A2*	-	ED22-A4	ED33-A2	-	ED32-A4
KL4E125***	ED5-A2	-	ED17-A4	ED20-A2*	-	ED22-A4	ED33-A2	-	ED32-A4
KL4E141***	ED6-A2	-	ED17-A4	ED23-A2*	-	ED22-A4	ED35-A2	-	ED32-A4
KL4E155***	ED6-A2	ED11-B2	ED17-A4	ED23-A2*	ED21-B2*	ED22-A4	ED35-A2	ED33-B2	ED32-A4
KL4E195***	ED7-A2	ED11-B2	ED17-A4	ED23-A2*	ED23-B2*	ED22-A4	ED35-A2	ED35-B2	ED34-A4
KL4E230***	ED7-A2	ED11-B2	ED17-A4	ED23-A2*	ED23-B2*	ED22-A4	ED35-A2	ED35-B2	ED34-A4

* 1/2 through 3 HP condensing units require ED210 or ED213 for systems with 2 evaporators. ED213 is not large enough for use with six-fan evaporators.

- Not available.

See additional notes on page 9.

ELECTRIC DEFROST KIT NOMENCLATURE

ED 12 - A2

Defrost Heater Voltage (2 = 208-230V, 4 = 460V)

Defrost Heater Phase (1 or 3)

A = 1 Phase Fan Motors, 1 Phase Heaters

B = 1 Phase Fan Motors, 3 Phase Heaters

C = 3 Phase Fan Motors, 3 Phase Heaters

Defrost Kit Identifier

Evaporator Quantity (1, 2, or 3 per system)

Kit Designator

Electric Defrost Kits

KIT NUMBER	TIMER	AUXILIARY SWITCH	BLOCK-OUT RELAY	DEFROST CONTACTOR	FAN CONTACTOR	SEQUENCING RELAY
ED5-230/1	1	—	1-15A	—	—	—
ED6-230/1	1	—	1-20A	—	—	—
ED7-230/1	1	—	1-25A	—	—	—
ED10-230/1	1	—	1-30A	—	—	—
ED11-230/3	1	1	—	1-30A	—	—
ED17-460/1	1	1	—	1-15A	1-15A	—
ED18-460/1	1	1	—	1-20A	1-20A	—
ED12-460/1	1	1	—	1-30A	1-25A	—
¹ ED210-230/1	1	—	1-30A	—	—	—
¹ ED213-230/1	1	1	—	1-50A	—	—
¹ ED213-230/3	1	1	—	1-50A	—	—
ED20-230/1	1	—	1-30A	—	—	2
ED22-460/1	1	1	—	2-15A	1-25A	2
ED23-230/1	1	1	—	2-25A	—	2
ED23-230/3	1	1	—	2-25A	—	2
ED30-230/1	1	—	1-30A	—	—	3
ED32-460/1	1	1	—	3-10A	1-25A	3
ED33-230/1	1	1	—	3-16A	—	3
ED34-460/1	1	1	—	3-16A	1-25A	3
ED35-230/1	1	1	—	3-33A	—	3
ED35-230/3	1	1	—	3-33A	—	3

Electric defrost kits consist of components that are necessary to control the defrost cycle. The kits are available as a factory installed option when ordered with a condensing unit. Not all Ed-Kits are available for all condensing unit models. The contents of each kit is described below, along with the function of each component.

Timer: Initiates the defrost cycle. Also used as a override protection for defrost termination.

Auxiliary Switch: It's mounted on the compressor contactor and prevents the defrost contactor from operating whenever the compressor is energized.

Block-Out Relay: Serves the same function as auxiliary switch. Used when defrost contactor is not required (lower wattage single phase only).

Defrost Contactor: Carries amperage load for heaters.

Fan Contactor: Used with 460V motors or when 230V motors are wired 3 phase.

Sequencing Relays: Provides interconnection of multiple unit coolers on a single system so that each unit cooler is allowed to individually terminate defrost on temperature.

— Not available.

¹ For use with 2 evaporators , 1/2 through 3 HP Next-Gen K-Series systems ONLY! ED213 is not large enough for six-fan evaporators.



NEXT-GEN ALL-TEMP


Performance and Electrical Data - Hot Gas Defrost - 6 FPI

Hot Gas 3-Pipe Model Number	Hot Gas Reverse Cycle 2-Pipe Model Number	BTUH Capacity @ -20°F S.T. & 10°FTD ¹		CFM	No. of Fans	Total Fan Motor AMPS - 1 Phase				MCA	MOPD				
		EC Motors [†]				PSC Motors									
		115V	208- 230V			115V	208- 230V	460V							
KL6H035***	KL6G035***	3,500	4,000	800	1	0.8	0.5	0.8	0.5	0.4					
KL6H042***	KL6G042***	4,200	4,900	785	1	0.8	0.5	0.8	0.5	0.4	15.0				
KL6H049***	KL6G049***	4,900	5,600	775	1	0.8	0.5	0.8	0.5	0.4	20				
KL6H066***	KL6G066***	6,600	7,600	1,600	2	1.6	1.0	1.6	1.0	0.8					
KL6H077***	KL6G077***	7,700	8,800	1,570	2	1.6	1.0	1.6	1.0	0.8	15.0				
KL6H090***	KL6G090***	9,000	10,600	1,550	2	1.6	1.0	1.6	1.0	0.8	20				
KL6H105***	KL6G105***	10,500	12,400	1,550	2	1.6	1.0	1.6	1.0	0.8					
KL6H121***	KL6G121***	12,100	14,200	2,355	3	2.4	1.5	2.4	1.5	1.2	15.0				
KL6H142***	KL6G142***	14,200	16,600	2,325	3	2.4	1.5	2.4	1.5	1.2	20				
KL6H162***	KL6G162***	16,200	18,700	3,140	4	3.2	2.0	3.2	2.0	1.6					
KL6H182***	KL6G182***	18,200	21,000	3,100	4	3.2	2.0	3.2	2.0	1.6	15.0				
KL6H200***	KL6G200***	20,000	22,800	3,925	5	4.0	2.5	4.0	2.5	2.0	20				
KL6H244***	KL6G244***	24,400	27,900	4,710	6	4.8	3.0	4.8	3.0	2.4					
KL6H281***	KL6G281***	28,100	33,000	4,650	6	4.8	3.0	4.8	3.0	2.4	15.0				

Hot Gas 3-Pipe Model Number	Hot Gas Reverse Cycle 2-Pipe Model Number	Drain Pan Heater Amps			Drain Pan Heater Watts
		115V	230V	460V	
		1PH	1PH	1PH	
KL6H035***	KL6G035***	3.1	1.7	0.9	375
KL6H042***	KL6G042***	3.1	1.7	0.9	375
KL6H049***	KL6G049***	3.1	1.7	0.9	375
KL6H066***	KL6G066***	6.3	3.3	1.7	750
KL6H077***	KL6G077***	6.3	3.3	1.7	750
KL6H090***	KL6G090***	6.3	3.3	1.7	750
KL6H105***	KL6G105***	6.3	3.3	1.7	750
KL6H121***	KL6G121***	9.3	4.8	2.4	1,100
KL6H142***	KL6G142***	9.3	4.8	2.4	1,100
KL6H162***	KL6G162***	12.3	6.4	3.2	1,475
KL6H182***	KL6G182***	12.3	6.4	3.2	1,475
KL6H200***	KL6G200***	15.4	8.1	4.0	1,850
KL6H244***	KL6G244***	18.5	9.7	4.9	2,225
KL6H281***	KL6G281***	18.5	9.7	4.9	2,225

Hot Gas 3-Pipe Model

The system uses 3 pipes — 1 for liquid line, 1 for suction line and 1 for hot gas. The hot gas is taken from the discharge line, between the compressor and the condenser, through a hot-gas solenoid valve to the distributor tee then through the coil.

**¹ Capacity Correction for Electric and Hot Gas Defrost Evaporators**

S.S.T. (Dew)	20°F	0°F	-10°F	-20°F	-30°F
Multiply Capacity by:	1.15	1.075	1.0375	1	0.9625

Use EC motors for 50 Hz operation.

* Each asterisk represents a variable character based on voltage, motor and vintage ordered. See page 4 for nomenclature.

^ Refrigerants with large glides are rated at dew point temperature. Use R407A capacity ratings for R407C and R407F.

† These Electronically Commutated (EC) Motors are not available for 460V. EC Motors can be field or factory wired for dual-speed operation. Dual-speed EC motors are compliant with California Title 24 regulations.

Energy Independence and Security Act of 2007 specifies that walk-in coolers and freezers under 3,000 square feet that are manufactured after January 1, 2009 shall have evaporators with EC motors when they are single phase, less than 460 volt and less than 1 HP.


Performance and Electrical Data - Hot Gas Defrost - 4 FPI

Hot Gas 3-Pipe Model Number	Hot Gas Reverse Cycle 2-Pipe Model Number	BTUH Capacity @ -20°F S.T. & 10°F TD ¹		CFM	No. of Fans	Total Fan Motor AMPS - 1 Phase				MCA	MOPD				
		EC Motors [†]				PSC Motors									
		115V	208- 230V			115V	208- 230V	460V							
KL4H027***	KL4G027***	2,700	3,100	800	1	0.8	0.5	0.8	0.5	0.4					
KL4H032***	KL4G032***	3,200	3,800	785	1	0.8	0.5	0.8	0.5	0.4	15.0				
KL4H038***	KL4G038***	3,800	4,400	775	1	0.8	0.5	0.8	0.5	0.4	20.0				
KL4H051***	KL4G051***	5,100	5,900	1,600	2	1.6	1.0	1.6	1.0	0.8					
KL4H064***	KL4G064***	6,400	7,300	1,570	2	1.6	1.0	1.6	1.0	0.8	15.0				
KL4H080***	KL4G080***	8,000	9,500	1,550	2	1.6	1.0	1.6	1.0	0.8	20.0				
KL4H094***	KL4G094***	9,400	11,000	2,355	3	2.4	1.5	2.4	1.5	1.2					
KL4H110***	KL4G110***	11,000	12,800	2,325	3	2.4	1.5	2.4	1.5	1.2	15.0				
KL4H125***	KL4G125***	12,500	14,400	3,140	4	3.2	2.0	3.2	2.0	1.6	20.0				
KL4H141***	KL4G141***	14,100	16,300	3,100	4	3.2	2.0	3.2	2.0	1.6					
KL4H155***	KL4G155***	15,500	17,700	3,925	5	4.0	2.5	4.0	2.5	2.0					
KL4H195***	KL4G195***	19,500	22,300	4,710	6	4.8	3.0	4.8	3.0	2.4	15.0				
KL4H230***	KL4G230***	23,000	27,000	4,650	6	4.8	3.0	4.8	3.0	2.4	20.0				

Hot Gas 3-Pipe Model Number	Hot Gas Reverse Cycle 2-Pipe Model Number	Drain Pan Heater Amps			Drain Pan Heater Watts
		115V	230V	460V	
		1PH	1PH	1PH	
KL4H027***	KL4G027***	3.1	1.7	0.9	375
KL4H032***	KL4G032***	3.1	1.7	0.9	375
KL4H038***	KL4G038***	3.1	1.7	0.9	375
KL4H051***	KL4G051***	6.3	3.3	1.7	750
KL4H064***	KL4G064***	6.3	3.3	1.7	750
KL4H080***	KL4G080***	6.3	3.3	1.7	750
KL4H094***	KL4G094***	9.3	4.8	2.4	1,100
KL4H110***	KL4G110***	9.3	4.8	2.4	1,100
KL4H125***	KL4G125***	12.3	6.4	3.2	1,475
KL4H141***	KL4G141***	12.3	6.4	3.2	1,475
KL4H155***	KL4G155***	15.4	8.1	4.0	1,850
KL4H195***	KL4G195***	18.5	9.7	4.9	2,225
KL4H230***	KL4G230***	18.5	9.7	4.9	2,225

Hot Gas Reverse Cycle 2-Pipe Model

A changeover valve is located in the discharge suction line of the compressor, so that when defrost is required, the valve changes over from the normal refrigeration flow so that the discharged gas flows into the suction connection and bypasses TX valve.

**¹ Capacity Correction for Electric and Hot Gas Defrost Evaporators**

S.S.T. (Dew)	20°F	0°F	-10°F	-20°F	-30°F
Multiply Capacity by:	1.15	1.075	1.0375	1	0.9625

Use EC motors for 50 Hz operation.

* Each asterisk represents a variable character based on voltage, motor and vintage ordered. See page 4 for nomenclature.

[^] Refrigerants with large glides are rated at dew point temperature. Use R407A capacity ratings for R407C and R407F.

[†] These Electronically Commutated (EC) Motors are not available for 460V. EC Motors can be field or factory wired for dual-speed operation. Dual-speed EC motors are compliant with California Title 24 regulations.

Energy Independence and Security Act of 2007 specifies that walk-in coolers and freezers under 3,000 square feet that are manufactured after January 1, 2009 shall have evaporators with EC motors when they are single phase, less than 460 volt and less than 1 HP.

Distributor Nozzle and Expansion Valves - Air Defrost Models

Model Number	Part Numbers						No. of Circuits	
	Nozzle @ Liq. Temp.		TXV ^A @ Liq. Temp.		EEV @ Liq. Temp.			
	50°F	100°F	50°F	100°F	50°F	100°F		

R404A

6 FPI	KL6A041***	-	-	SBFSE-AAA-C	SBFSE-AAA-C	SER-AA	SER-AA	1
	KL6A052***	-	-	SBFSE-AAA-C	SBFSE-AAA-C	SER-AA	SER-AA	1
	KL6A066***	L, #1/9	L, #1/3	SBFSE-AAA-C	SBFSE-AA-C	SER-AA	SER-AA	2
	KL6A073***	L, #1/6	L, #1/3	SBFSE-AAA-C	SBFSE-AA-C	SER-AA	SER-AA	2
	KL6A094***	L, #1/6	L, #1/2	SBFSE-AA-C	SBFSE-A-C	SER-AA	SER-A	2
	KL6A117***	L, #1/4	L, #3/4	SBFSE-AA-C	SBFSE-A-C	SER-A	SER-A	3
	KL6A130***	L, #1/4	L, #3/4	SBFSE-AA-C	SBFSE-A-C	SER-A	SER-A	3
	KL6A141***	L, #1/4	L, #3/4	SBFSE-A-C	SBFSE-A-C	SER-A	SER-A	4
	KL6A161***	L, #1/4	L, #3/4	SBFSE-A-C	SBFSE-A-C	SER-A	SER-A	3
	KL6A181***	L, #1/3	L, #1	SBFSE-A-C	SBFSE-A-C	SER-A	SER-B	4
	KL6A195***	L, #1/3	L, #1	SBFSE-A-C	SBFSE-A-C	SER-A	SER-B	4
	KL6A235***	L, #1/3	L, #1	SBFSE-A-C	SBFSE-B-C	SER-A	SER-B	6
	KL6A260***	L, #1/2	L, #1-1/2	SBFSE-A-C	SBFSE-B-C	SER-B	SER-B	6
	KL6A295***	L, #1/2	L, #1-1/2	SBFSE-B-C	SBFSE-B-C	SER-B	SER-B	8
	KL6A330***	L, #3/4	L, #2	SBFSE-B-C	SBFSE-B-C	SER-B	SER-C	7
	KL6A390***	L, #3/4	L, #2	SBFSE-B-C	SBFSE-B-C	SER-B	SER-C	8

R407A/ R448A/ R449A/Bt

6 FPI	KL6A041***	-	-	SBFDE-AAA-C	SBFDE-AAA-C	SER-AA	SER-AA	1
	KL6A052***	-	-	SBFDE-AAA-C	SBFDE-AAA-C	SER-AA	SER-AA	1
	KL6A066***	L, #1/6	L, #1/3	SBFDE-AAA-C	SBFDE-AA-C	SER-AA	SER-AA	2
	KL6A073***	L, #1/6	L, #1/3	SBFDE-AA-C	SBFDE-AA-C	SER-AA	SER-AA	2
	KL6A094***	L, #1/4	L, #1/2	SBFDE-AA-C	SBFDE-AA-C	SER-AA	SER-A	2
	KL6A117***	L, #1/4	L, #3/4	SBFDE-AA-C	SBFDE-A-C	SER-A	SER-A	3
	KL6A130***	L, #1/4	L, #3/4	SBFDE-AA-C	SBFDE-A-C	SER-A	SER-A	3
	KL6A141***	L, #1/3	L, #3/4	SBFDE-AA-C	SBFDE-A-C	SER-A	SER-A	4
	KL6A161***	L, #1/3	L, #3/4	SBFDE-AA-C	SBFDE-A-C	SER-A	SER-A	3
	KL6A181***	L, #1/2	L, #1	SBFDE-A-C	SBFDE-A-C	SER-A	SER-B	4
	KL6A195***	L, #1/2	L, #1	SBFDE-A-C	SBFDE-A-C	SER-A	SER-B	4
	KL6A235***	L, #1/2	L, #1-1/2	SBFDE-A-C	SBFDE-A-C	SER-A	SER-B	6
	KL6A260***	L, #3/4	L, #1-1/2	SBFDE-A-C	SBFDE-B-C	SER-B	SER-B	6
	KL6A295***	L, #3/4	L, #2	SBFDE-B-C	SBFDE-B-C	SER-B	SER-C	8
	KL6A330***	L, #3/4	L, #2	SBFDE-B-C	SBFDE-B-C	SER-B	SER-C	7
	KL6A390***	L, #1	L, #2	SBFDE-B-C	SBFDE-B-C	SER-B	SER-C	8

Distributor lines are 3/16" diameter and 14" long. Distributor connection size is 1/2" for all air defrost models.

* Each asterisk represents a variable character based on voltage, motor and vintage ordered. See page 4 for nomenclature.

- Single feed circuit coils do not get a distributor/nozzle.

^A TXV selections are based on +25°F suction temp., 8°F to 12°F evaporator TD. Contact factory for operating conditions outside of this range.

† SBFDE expansion valves are compatible with R407A, R448A and R449A/B. For other valves, follow manufacturers selection guidelines.

Base models (no factory-mounted components) include nozzles sized for 100°F liquid shipped loose.

Distributor Nozzle and Expansion Valves - Electric Defrost Models

Model Number	Part Numbers						No. of Circuits	
	Nozzle @ Liq. Temp.		TXV ^A @ Liq. Temp.		EEV @ Liq. Temp.			
	50°F	100°F	50°F	100°F	50°F	100°F		
R404A								
6 FPI	KL6E035***	-	-	SBFSE-AAA-ZP	SBFSE-AAA-ZP	SER-AA	SER-AA 1	
	KL6E042***	L, #1/4	L, #1/2	SBFSE-AAA-ZP	SBFSE-AA-ZP	SER-AA	SER-AA 2	
	KL6E049***	L, #1/4	L, #1/2	SBFSE-AA-ZP	SBFSE-AA-ZP	SER-AA	SER-AA 2	
	KL6E066***	L, #1/4	L, #1/2	SBFSE-AA-ZP	SBFSE-A-ZP	SER-AA	SER-AA 2	
	KL6E077***	L, #1/3	L, #3/4	SBFSE-AA-ZP	SBFSE-A-ZP	SER-AA	SER-A 3	
	KL6E090***	L, #1/2	L, #1	SBFSE-AA-ZP	SBFSE-A-ZP	SER-AA	SER-A 5	
	KL6E105***	L, #1/2	L, #1	SBFSE-A-ZP	SBFSE-A-ZP	SER-A	SER-A 6	
	KL6E121***	L, #3/4	L, #1-1/2	SBFSE-A-ZP	SBFSE-A-ZP	SER-A	SER-A 6	
	KL6E142***	L, #3/4	L, #1-1/2	SBFSE-A-ZP	SBFSE-B-ZP	SER-A	SER-B 6	
4 FPI	KL6E162***	L, #3/4	L, #1-1/2	SBFSE-A-ZP	SBFSE-B-ZP	SER-A	SER-B 6	
	KL6E182***	L, #1	L, #2	SBFSE-A-ZP	SBFSE-B-ZP	SER-A	SER-B 6	
	KL6E200***	L, #1	L, #2	SBFSE-A-ZP	SBFSE-B-ZP	SER-A	SER-B 6	
	KL6E244***	L, #1-1/2	L, #2-1/2	SBFSE-B-ZP	SBFSE-C-ZP	SER-B	SER-C 9	
	KL6E281***	G, #1-1/2	G, #2-1/2	SBFSE-C-ZP	SBFSE-C-ZP	SER-B	SER-C 12	
	KL4E027***	-	-	SBFSE-AAA-ZP	SBFSE-AAA-ZP	SER-AA	SER-AA 1	
	KL4E032***	-	-	SBFSE-AAA-ZP	SBFSE-AAA-ZP	SER-AA	SER-AA 1	
	KL4E038***	L, #1/6	L, #1/3	SBFSE-AAA-ZP	SBFSE-AA-ZP	SER-AA	SER-AA 2	
	KL4E051***	L, #1/4	L, #1/2	SBFSE-AA-ZP	SBFSE-AA-ZP	SER-AA	SER-AA 2	
4 FPI	KL4E064***	L, #1/3	L, #3/4	SBFSE-AA-ZP	SBFSE-A-ZP	SER-AA	SER-A 3	
	KL4E080***	L, #1/2	L, #1	SBFSE-AA-ZP	SBFSE-A-ZP	SER-AA	SER-A 6	
	KL4E094***	L, #1/2	L, #1	SBFSE-A-ZP	SBFSE-A-ZP	SER-A	SER-A 6	
	KL4E110***	L, #3/4	L, #1-1/2	SBFSE-A-ZP	SBFSE-A-ZP	SER-A	SER-A 6	
	KL4E125***	L, #3/4	L, #1-1/2	SBFSE-A-ZP	SBFSE-A-ZP	SER-A	SER-A 6	
	KL4E141***	L, #3/4	L, #1-1/2	SBFSE-A-ZP	SBFSE-B-ZP	SER-A	SER-B 6	
	KL4E155***	L, #3/4	L, #1-1/2	SBFSE-A-ZP	SBFSE-B-ZP	SER-A	SER-B 6	
	KL4E195***	L, #1	L, #2	SBFSE-A-ZP	SBFSE-B-ZP	SER-A	SER-B 9	
	KL4E230***	G, #1	G, #2-1/2	SBFSE-C-ZP	SBFSE-C-ZP	SER-B	SER-B 12	
R407A/ R448A/ R449A/Bt								
6 FPI	KL6E035***	-	-	SBFDE-AAA-ZP	SBFDE-AAA-ZP	SER-AA	SER-AA 1	
	KL6E042***	L, #1/4	L, #1/2	SBFDE-AAA-ZP	SBFDE-AA-ZP	SER-AA	SER-AA 2	
	KL6E049***	L, #1/4	L, #1/2	SBFDE-AA-ZP	SBFDE-AA-ZP	SER-AA	SER-AA 2	
	KL6E066***	L, #1/4	L, #1/2	SBFDE-AA-ZP	SBFDE-AA-ZP	SER-AA	SER-AA 2	
	KL6E077***	L, #1/2	L, #3/4	SBFDE-AA-ZP	SBFDE-A-ZP	SER-AA	SER-A 3	
	KL6E090***	L, #1/2	L, #1	SBFDE-AA-ZP	SBFDE-A-ZP	SER-AA	SER-A 5	
	KL6E105***	L, #3/4	L, #1	SBFDE-A-ZP	SBFDE-B-ZP	SER-A	SER-A 6	
	KL6E121***	L, #3/4	L, #1-1/2	SBFDE-A-ZP	SBFDE-B-ZP	SER-A	SER-A 6	
	KL6E142***	L, #3/4	L, #1-1/2	SBFDE-B-ZP	SBFDE-B-ZP	SER-A	SER-B 6	
4 FPI	KL6E162***	L, #1	L, #1-1/2	SBFDE-B-ZP	SBFDE-B-ZP	SER-A	SER-B 6	
	KL6E182***	L, #1	L, #2	SBFDE-B-ZP	SBFDE-B-ZP	SER-A	SER-B 6	
	KL6E200***	L, #1	L, #2	SBFDE-B-ZP	SBFDE-B-ZP	SER-A	SER-B 6	
	KL6E244***	L, #1-1/2	L, #2	SBFDE-B-ZP	SBFDE-B-ZP	SER-B	SER-B 9	
	KL6E281***	G, #1-1/2	G, #2-1/2	SBFDE-C-ZP	SBFDE-C-ZP	SER-B	SER-C 12	
	KL4E027***	-	-	SBFDE-AAA-ZP	SBFDE-AAA-ZP	SER-AA	SER-AA 1	
	KL4E032***	-	-	SBFDE-AAA-ZP	SBFDE-AAA-ZP	SER-AA	SER-AA 1	
	KL4E038***	L, #1/4	L, #1/3	SBFDE-AAA-ZP	SBFDE-AA-ZP	SER-AA	SER-AA 2	
	KL4E051***	L, #1/4	L, #1/2	SBFDE-AA-ZP	SBFDE-AA-ZP	SER-AA	SER-AA 2	
4 FPI	KL4E064***	L, #1/3	L, #3/4	SBFDE-AA-ZP	SBFDE-AA-ZP	SER-AA	SER-AA 3	
	KL4E080***	L, #1/2	L, #1	SBFDE-AA-ZP	SBFDE-A-ZP	SER-AA	SER-A 6	
	KL4E094***	L, #1/2	L, #1	SBFDE-A-ZP	SBFDE-A-ZP	SER-A	SER-A 6	
	KL4E110***	L, #3/4	L, #1-1/2	SBFDE-A-ZP	SBFDE-A-ZP	SER-A	SER-A 6	
	KL4E125***	L, #3/4	L, #1-1/2	SBFDE-A-ZP	SBFDE-B-ZP	SER-A	SER-A 6	
	KL4E141***	L, #3/4	L, #1-1/2	SBFDE-A-ZP	SBFDE-B-ZP	SER-A	SER-B 6	
	KL4E155***	L, #3/4	L, #1-1/2	SBFDE-B-ZP	SBFDE-B-ZP	SER-A	SER-B 6	
	KL4E195***	L, #1	L, #2	SBFDE-B-ZP	SBFDE-B-ZP	SER-A	SER-B 9	
	KL4E230***	G, #1-1/2	G, #2-1/2	SBFDE-C-ZP	SBFDE-C-ZP	SER-B	SER-B 12	

Distributor lines are 3/16" diameter and 14" long. Distributor connection size is 1/2" for electric defrost models with "L" nozzle and 7/8" for models with "G" nozzle.

* Each asterisk represents a variable character based on voltage, motor and vintage ordered. See page 4 for nomenclature.

- Single feed circuit coils do not get a distributor/nozzle.

^A TXV selections are based on -20°F suction temp., 8°F to 12°F evaporator TD. Contact factory for operating conditions outside of this range. Do not use pressure limiting TXVs when the condensing unit includes a CPR valve.

^T SBFDE expansion valves are compatible with R407A, R448A and R449A/B. For other valves, follow manufacturers selection guidelines.

Base models (no factory-mounted components) include nozzles sized for 100°F liquid shipped loose.

Distributor Nozzle and Expansion Valves Hot Gas Defrost Models

Hot Gas 3-Pipe Model Number	Hot Gas Reverse Cycle 2-Pipe Model Number	Part Numbers						No. of Circuits	
		Nozzle @ Liq. Temp.		TXV ^a @ Liq. Temp.		EEV @ Liq. Temp.			
		50°F	100°F	50°F	100°F	50°F	100°F		

R404A

6 FPI	KL6H035***	KL6G035***	—	—	SBFSE-AAA-ZP	SBFSE-AAA-ZP	SER-AA	SER-AA	1
	KL6H042***	KL6G042***	L, #1/4	L, #1/2	SBFSE-AAA-ZP	SBFSE-AA-ZP	SER-AA	SER-AA	2
	KL6H049***	KL6G049***	L, #1/4	L, #1/2	SBFSE-AA-ZP	SBFSE-AA-ZP	SER-AA	SER-AA	2
	KL6H066***	KL6G066***	L, #1/3	L, #3/4	SBFSE-AA-ZP	SBFSE-AA-ZP	SER-AA	SER-AA	2
	KL6H077***	KL6G077***	L, #1/2	L, #1	SBFSE-AA-ZP	SBFSE-A-ZP	SER-AA	SER-A	3
	KL6H090***	KL6G090***	L, #1/2	L, #1	SBFSE-AA-ZP	SBFSE-A-ZP	SER-AA	SER-A	5
	KL6H105***	KL6G105***	L, #1/2	L, #1-1/2	SBFSE-A-ZP	SBFSE-A-ZP	SER-A	SER-A	6
	KL6H121***	KL6G121***	L, #3/4	L, #1-1/2	SBFSE-A-ZP	SBFSE-B-ZP	SER-A	SER-A	6
	KL6H142***	KL6G142***	L, #1	L, #2	SBFSE-A-ZP	SBFSE-B-ZP	SER-A	SER-B	6
	KL6H162***	KL6G162***	L, #1	L, #2	SBFSE-A-ZP	SBFSE-B-ZP	SER-A	SER-B	6
	KL6H182***	KL6G182***	L, #1	L, #2	SBFSE-A-ZP	SBFSE-B-ZP	SER-A	SER-B	6
	KL6H200***	KL6G200***	L, #1	L, #2	SBFSE-A-ZP	SBFSE-B-ZP	SER-A	SER-B	6
	KL6H244***	KL6G244***	E, #1-1/2	E(R), #3	SBFSE-C-ZP	SBFSE-C-ZP	SER-B	SER-C	9
	KL6H281***	KL6G281***	E, #1-1/2	E(R), #3	SBFSE-C-ZP	SBFSE-C-ZP	SER-B	SER-C	12
4 FPI	KL4H027***	KL4G027***	—	—	SBFSE-AAA-ZP	SBFSE-AAA-ZP	SER-AA	SER-AA	1
	KL4H032***	KL4G032***	—	—	SBFSE-AAA-ZP	SBFSE-AAA-ZP	SER-AA	SER-AA	1
	KL4H038***	KL4G038***	L, #1/4	L, #1/2	SBFSE-AAA-ZP	SBFSE-AA-ZP	SER-AA	SER-AA	2
	KL4H051***	KL4G051***	L, #1/4	L, #1/2	SBFSE-AAA-ZP	SBFSE-AA-ZP	SER-AA	SER-AA	2
	KL4H064***	KL4G064***	L, #1/3	L, #3/4	SBFSE-AA-ZP	SBFSE-A-ZP	SER-AA	SER-A	3
	KL4H080***	KL4G080***	L, #1/2	L, #1	SBFSE-AA-ZP	SBFSE-A-ZP	SER-AA	SER-A	6
	KL4H094***	KL4G094***	L, #1/2	L, #1	SBFSE-A-ZP	SBFSE-A-ZP	SER-A	SER-A	6
	KL4H110***	KL4G110***	L, #3/4	L, #1-1/2	SBFSE-A-ZP	SBFSE-A-ZP	SER-A	SER-A	6
	KL4H125***	KL4G125***	L, #3/4	L, #1-1/2	SBFSE-A-ZP	SBFSE-A-ZP	SER-A	SER-A	6
	KL4H141***	KL4G141***	L, #3/4	L, #1-1/2	SBFSE-A-ZP	SBFSE-B-ZP	SER-A	SER-B	6
	KL4H155***	KL4G155***	L, #3/4	L, #2	SBFSE-A-ZP	SBFSE-B-ZP	SER-A	SER-B	6
	KL4H195***	KL4G195***	E, #1	E(R), #2-1/2	SBFSE-C-ZP	SBFSE-C-ZP	SER-A	SER-B	9
	KL4H230***	KL4G230***	E, #1-1/2	E(R), #3	SBFSE-C-ZP	SBFSE-C-ZP	SER-B	SER-B	12

R407A/ R448A/ R449A/Bt

6 FPI	KL6H035***	KL6G035***	—	—	SBFDE-AAA-ZP	SBFDE-AAA-ZP	SER-AA	SER-AA	1
	KL6H042***	KL6G042***	L, #1/4	L, #1/2	SBFDE-AA-ZP	SBFDE-AA-ZP	SER-AA	SER-AA	2
	KL6H049***	KL6G049***	L, #1/3	L, #1/2	SBFDE-AA-ZP	SBFDE-AA-ZP	SER-AA	SER-AA	2
	KL6H066***	KL6G066***	L, #1/3	L, #3/4	SBFDE-AA-ZP	SBFDE-AA-ZP	SER-AA	SER-AA	2
	KL6H077***	KL6G077***	L, #1/2	L, #3/4	SBFDE-AA-ZP	SBFDE-A-ZP	SER-AA	SER-A	3
	KL6H090***	KL6G090***	L, #1/2	L, #1	SBFDE-AA-ZP	SBFDE-A-ZP	SER-AA	SER-A	5
	KL6H105***	KL6G105***	L, #3/4	L, #1-1/2	SBFDE-A-ZP	SBFDE-A-ZP	SER-A	SER-A	6
	KL6H121***	KL6G121***	L, #3/4	L, #1-1/2	SBFDE-A-ZP	SBFDE-B-ZP	SER-A	SER-A	6
	KL6H142***	KL6G142***	L, #1	L, #2	SBFDE-B-ZP	SBFDE-B-ZP	SER-A	SER-B	6
	KL6H162***	KL6G162***	L, #1	L, #2	SBFDE-B-ZP	SBFDE-B-ZP	SER-A	SER-B	6
	KL6H182***	KL6G182***	L, #1	L, #2	SBFDE-B-ZP	SBFDE-B-ZP	SER-A	SER-B	6
	KL6H200***	KL6G200***	L, #1	L, #2	SBFDE-B-ZP	SBFDE-B-ZP	SER-A	SER-B	6
	KL6H244***	KL6G244***	E, #1-1/2	E(R), #3	SBFDE-C-ZP	SBFDE-C-ZP	SER-B	SER-B	9
	KL6H281***	KL6G281***	E, #2	E(R), #3	SBFDE-C-ZP	SBFDE-C-ZP	SER-B	SER-C	12
4 FPI	KL4H027***	KL4G027***	—	—	SBFDE-AAA-ZP	SBFDE-AAA-ZP	SER-AA	SER-AA	1
	KL4H032***	KL4G032***	—	—	SBFDE-AAA-ZP	SBFDE-AAA-ZP	SER-AA	SER-AA	1
	KL4H038***	KL4G038***	L, #1/4	L, #1/2	SBFDE-AA-ZP	SBFDE-AA-ZP	SER-AA	SER-AA	2
	KL4H051***	KL4G051***	L, #1/3	L, #3/4	SBFDE-AA-ZP	SBFDE-AA-ZP	SER-AA	SER-AA	2
	KL4H064***	KL4G064***	L, #1/2	L, #3/4	SBFDE-AA-ZP	SBFDE-A-ZP	SER-AA	SER-AA	3
	KL4H080***	KL4G080***	L, #1/2	L, #1	SBFDE-AA-ZP	SBFDE-A-ZP	SER-AA	SER-A	6
	KL4H094***	KL4G094***	L, #3/4	L, #1-1/2	SBFDE-A-ZP	SBFDE-B-ZP	SER-A	SER-A	6
	KL4H110***	KL4G110***	L, #3/4	L, #1-1/2	SBFDE-A-ZP	SBFDE-B-ZP	SER-A	SER-A	6
	KL4H125***	KL4G125***	L, #1	L, #1-1/2	SBFDE-A-ZP	SBFDE-B-ZP	SER-A	SER-A	6
	KL4H141***	KL4G141***	L, #1	L, #2	SBFDE-B-ZP	SBFDE-B-ZP	SER-A	SER-B	6
	KL4H155***	KL4G155***	L, #1	L, #2	SBFDE-B-ZP	SBFDE-B-ZP	SER-A	SER-B	6
	KL4H195***	KL4G195***	E, #1-1/2	E(R), #2-1/2	SBFDE-C-ZP	SBFDE-C-ZP	SER-A	SER-B	9
	KL4H230***	KL4G230***	E, #1-1/2	E(R), #3	SBFDE-C-ZP	SBFDE-C-ZP	SER-B	SER-B	12

Distributor lines are 1/4" diameter and 14" long. Distributor connection size is 1/2" for all hot gas defrost models with "L" nozzle and 1-1/8" for models with "E" nozzle.

* Each asterisk represents a variable character based on voltage, motor and vintage ordered. See page 4 for nomenclature.

- Single feed circuit coils do not get a distributor/nozzle.

^a TXV selections are based on -20°F suction temp., 8°F to 12°F evaporator TD. Contact factory for operating conditions outside of this range.

Do not use pressure limiting TXVs when the condensing unit includes a CPR valve.

† SBFDE expansion valves are compatible with R407A, R448A and R449A/B. For other valves, follow manufacturers selection guidelines.

Base models (no factory-mounted components) include nozzles sized for 100°F liquid shipped loose.

Specifications

Models		TXV [†] Type	Refrigerant Connections			No. of Hanger Slot Locations	Dimensions (Inches)				Approx. Ship Wt. (Lbs.)
KL6A	KL*E/G/H		LIQ. LINE [‡]	KL6A SUCT.	KL*E/G/H SUCT.		A [§]	B [§]	C [§]	W	

6 FPI

KL6A041***	KL6*035***	EXT	3/8	5/8	5/8	2	17-1/4	—	—	27-1/8	41
KL6A052***	KL6*042***	EXT	3/8	5/8	5/8	2	17-1/4	—	—	27-1/8	44
KL6A066***	KL6*049***	EXT	3/8	5/8	5/8	2	17-1/4	—	—	27-1/8	47
KL6A073***	KL6*066***	EXT	3/8	5/8	7/8	2	33-1/4	—	—	43-5/8	52
KL6A094***	KL6*077***	EXT	3/8	5/8	7/8	2	33-1/4	—	—	43-5/8	55
KL6A117***	KL6*090***	EXT	3/8	5/8	7/8	2	33-1/4	—	—	43-5/8	58
KL6A130***	KL6*105***	EXT	3/8	5/8	7/8	2	33-1/4	—	—	43-5/8	62
KL6A141***	—	EXT	3/8	5/8	—	2	49-1/4	—	—	60-1/8	72
KL6A161***	KL6*121***	EXT	3/8	5/8	1-1/8	2	49-1/4	—	—	60-1/8	78
KL6A181***	KL6*142***	EXT	3/8	7/8	1-1/8	2	49-1/4	—	—	60-1/8	85
KL6A195***	—	EXT	3/8	7/8	—	2	65-1/4	—	—	76-5/8	115
KL6A235***	KL6*162***	EXT	3/8	7/8	1-1/8	2	65-1/4	—	—	76-5/8	124
KL6A260***	KL6*182***	EXT	3/8	7/8	1-1/8	2	65-1/4	—	—	76-5/8	147
—	KL6*200***	EXT	3/8	—	1-1/8	3	81-1/4	32-5/8	48-5/8	93-1/8	195
KL6A295***	—	EXT	3/8	1-1/8	—	3	81-1/4	32-5/8	48-5/8	93-1/8	218
—	KL6*244***	EXT	3/8	—	1-1/8	3	97-1/4	48-5/8	48-5/8	109-5/8	238
KL6A330***	—	EXT	3/8	1-1/8	—	3	97-1/4	48-5/8	48-5/8	109-5/8	257
KL6A390***	KL6*281***	EXT	3/8	1-1/8	1-1/8	3	97-1/4	48-5/8	48-5/8	109-5/8	262

4 FPI

—	KL4*027***	EXT	3/8	—	5/8	2	17-1/4	—	—	27-1/8	40
—	KL4*032***	EXT	3/8	—	5/8	2	17-1/4	—	—	27-1/8	42
—	KL4*038***	EXT	3/8	—	5/8	2	17-1/4	—	—	27-1/8	46
—	KL4*051***	EXT	3/8	—	7/8	2	33-1/4	—	—	43-5/8	50
—	KL4*064***	EXT	3/8	—	7/8	2	33-1/4	—	—	43-5/8	52
—	KL4*080***	EXT	3/8	—	7/8	2	33-1/4	—	—	43-5/8	55
—	KL4*094***	EXT	3/8	—	1-1/8	2	49-1/4	—	—	60-1/8	79
—	KL4*110***	EXT	3/8	—	1-1/8	2	49-1/4	—	—	60-1/8	84
—	KL4*125***	EXT	3/8	—	1-1/8	2	65-1/4	—	—	76-5/8	124
—	KL4*141***	EXT	3/8	—	1-1/8	2	65-1/4	—	—	76-5/8	144
—	KL4*155***	EXT	3/8	—	1-1/8	3	81-1/4	32-5/8	48-5/8	93-1/8	191
—	KL4*195***	EXT	3/8	—	1-1/8	3	97-1/4	48-5/8	48-5/8	109-5/8	257
—	KL4*230***	EXT	3/8	—	1-1/8	3	97-1/4	48-5/8	48-5/8	109-5/8	262

* Each asterisk represents a variable character based on defrost, voltage, motor and vintage ordered. See page 4 for nomenclature.

— Not available.

[†] Externally equalized.

[‡] For units with mounted TXV components. See Nozzle/TXV table for distributor connection size when TXV is field installed.



[§] Dimensions listed are the distance between hanger slots. Hanger slots are 3/4" deep x 1/2" wide.

Physical Dimensions

Installation Notes:

- (1) Install 12" away from back wall.
- (2) Drain connection is located in the center/rear of the drain pan.
- (3) Standard refrigerant connections are located at the left rear (facing air discharge).

All dimensions are in inches.



NOTE: Refrigerant and electrical connection locations have been changed for the Next-Gen All-Temp design. Standard connections are now opposite of the legacy LP models.



Due to continuing product development, specifications are subject to change without notice.