

RUUD SALES FACT SHEET

R801T- SERIES 80% A.F.U.E.† Models with Input Rates of 75 to 125 kBTU [22 to 37 kW]



GENERAL TERMS OF LIMITED WARRANTY*

†A.F.U.E. (Annual Fuel Utilization Efficiency) calculated in accordance with Department of Energy test procedures.

*For complete details of the Limited and Conditional Warranties, including applicable terms and conditions, contact your local contractor or the Manufacturer for a copy of the product warranty certificate.

Ruud *Achiever Plus*™ Series Downflow Gas Furnace

Features

- 80% residential Gas Furnace CSA certified
- PlusOne[™] Diagnostics 7 Segment LED all units
- PlusOne[™] Ignition System DSI for reliability and longevity
- Heat exchanger is removable for improved serviceability. Aluminized steel construction provides maximum corrosion resistance and thermal fatigue reliability.
- Low profile 34" cabinet ideal for space constrained installations
- Integrated Control board features dip switches for easy system set up
- QR code for quick access to product information from your smart phone or tablet
- Insulated blower compartment
- Constant Torque electrically commutated motor

MODEL	INPUT- BTU/HR [kW]	HEATING CAPACITY BTU/HR [kW]	HEATING CFM @ .2" [.049 kPa] W.C. E.S.P. [L/s]	COOLING CFM @ .5" [.124 kPa] W.C. E.S.P. [L/s]	APPROX. SHIPPING WEIGHT (LBS.) [kg]	PRICE
R801TA075317Z*A	75,000 [22]	60,000 [18]	1333 [629]	1200 [566]	105 [48]	
R801TA075521Z*A	75,000 [22]	60,000 [18]	1564 [738]	2000 [944]	120 [54]	
R801TA100521Z*A	100,000 [29]	81,000 [24]	1877 [886]	2000 [944]	120 [54]	
R801TA125524Z*A	125,000 [37]	99,000 [29]	1859 [877]	2000 [944]	140 [63]	

[] Designates Metric Conversions











RUUD SALES FACT SHEET

R801T DOWNFLOW					
Description	Part No.	Price			
Filter Rack	RXGF-CC				
Combustible Floor Base for R801T075317	RXGC-B17				
Combustible Floor Base for R801TA100521, R801T075521	RXGC-B21				
Combustible Floor Base for R801T125	RXGC-B24				