



SALES FACT SHEET

Classic® S E R I E S



R410A
earth friendly refrigerant

RSNM- SERIES

13 SEER Series

Nominal Sizes 2-5 Tons [7-17.6 kW]

RSPM- SERIES

14 SEER Series

Nominal Sizes 2-5 Tons [7-17.6 kW]

Features

The *Rheem Classic® Series* RSNM-/RSPM- Package Air Conditioners can provide year-round heating and cooling comfort for residential, multi-family and light commercial applications.

The following additional features, plus its energy-saving characteristics, make the RSNM-/RSPM- Package Air Conditioner an excellent choice for new construction or upgrading your present system.

- Hi-Static Capability
- Indoor Coil access for easy cleaning
- Slide-out Indoor Blower for easy motor and blower maintenance
- Slide-out Drain Pan for easy access and cleaning
- Round Horizontal Supply & Return for application adaptability
- Duct Collars provided
- Condensate Trap provided
- Scroll Compressor
- Copper Tube/Aluminum Fin Coils
- Powder painted louvered steel cabinet protects coil from yard hazard damage
- Painted Base Pan
- Easily accessible Gauge Ports
- Spacious Control Box for easy accessibility
- Power and control wiring are kept separate
- Certified and rated under ARI Standard 210
- U.L. listed
- Zero clearance to structure
- Electric Heat Factory or Field Installed

GENERAL TERMS OF LIMITED WARRANTY

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Compressor (1 Phase Residential Applications)Ten (10) Years

Compressor (13 & 14 SEER Commercial Applications)Five (5) Years

*Conditional Parts (1 Phase Residential Applications)

(Registration Required)Ten (10) Years

*See Product Warranty Card for Details.

<u>R</u>	<u>S</u>	<u>N</u>	<u>M</u>	<u>—</u>	<u>A</u>	<u>036</u>	<u>J</u>	<u>K</u>	<u>010</u>
RHEEM	PRODUCT CLASSIFICATION	EFFICIENCY DESIGNATION (STANDARD)	DESIGN SERIES		FUTURE TECHNICAL VARIATIONS	COOLING CAPACITY	ELECTRICAL DESIGNATION	DRIVE PACKAGE	HEATING CAPACITY (RESISTANCE HEAT)
	S = PACKAGE AIR CONDITIONER	N = 13 SEER P = 14 SEER	M = R-410A			024 = 24,000 BTU/H [7.03 kW] 030 = 30,000 BTU/H [8.79 kW] 036 = 36,000 BTU/H [10.55 kW] 042 = 42,000 BTU/H [12.31 kW] 043 = 42,000 BTU/H [12.31 kW] 048 = 48,000 BTU/H [14.07 kW] 060 = 60,000 BTU/H [17.58 kW]	J = 208-230V— 1PH—60 Hz C = 208-230V— 3PH—60 Hz	K = DIRECT DRIVE	000 = NONE 005 = 05 KW 007 = 07 KW 010 = 10 KW 015 = 15 KW 020 = 20 KW

Price	Starting at: \$
-------	--------------------

