



SALES FACT SHEET



AIR HANDLERS

RHLA- High Efficiency

featuring R-22 Refrigerant

RHLL- High Efficiency

featuring New Industry Standard

R-410A Refrigerant **R-410A**

Features

- RHLA/RHLL models feature GE's new X-13 (ECM) motor which provides enhanced SEER performance with most Ruud outdoor units.
- 1 1/2 ton [5.3 kW] through 5 ton [17.6 kW] models are between 42 1/2 to 55 1/2 inches [1080 to 1410 mm] tall and 22 inches [559 mm] deep.
- Versatile 4-way convertible design for upflow, downflow, horizontal left and horizontal right applications.
- Factory-installed high efficiency indoor coil.
- All models meet or exceed 330 to 400 CFM [156 to 189 L/s] per ton at .3 inches [.7 kPa] of external static pressure.
- Enhanced airflow up to .7" external static pressure.
- Sturdy construction with 1.0 inch [.24 kPa] of reinforced foil faced jacket insulation for excellent thermal and sound insulation.
- Field-installed auxiliary electric heater kits provide exact heat for indoor comfort. Kits include circuit breakers which meet UL and cUL requirements for service disconnect.
- The most compact unit design available, all standard heat air handler models only 42 1/2 to 55 1/2 inches [1079 to 1409 mm] high.
- Attractive pre-painted cabinet exterior.
- Rugged wall steel cabinet construction, designed for added strength and versatility.

GENERAL TERMS OF LIMITED WARRANTY

Ruud will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Conditional Parts* (Registration Required) Ten (10) Years

*For Complete Details of the Limited Warranty, including Applicable Terms & Conditions, See Your Local Installer or Contact the Manufacturer for a Copy.

<u>R</u>	<u>H</u>	<u>L</u>	<u>A</u> — <u>HM</u>	<u>24</u>	<u>17</u>	<u>J</u>	<u>A</u>
RUUD	CLASSIFICATION	L =	REFRIGERANT	CAPACITY	CABINET SIZE	VOLTAGE	DESIGN VARIATION
	H =	HI-EFFICIENCY	A = R-22	24 = 18,000/24,000 BTU/HR	17 = 17.5" [431.8 mm]	A = 115/1/60	A =
	AIR HANDLER	(X-13 (ECM) MOTOR)	L = R-410A	[5.27/7.03 kW]	(800-1200 CFM)	J = 208/240/1/60	1ST DESIGN
				36 = 30,000/36,000 BTU/HR	21 = 21" [533.4 mm]		
				[6.79/10.55 kW]	(1400-1600 CFM)		
				48 = 42,000/48,000 BTU/HR	24 = 24.5" [609.6 mm]		
				[12.31/14.07 kW]	(1600-1800 CFM)		
				60 = 60,000 BTU/HR			
				[17.58 kW]			

Price

Starting at:
\$

