



SALES FACT SHEET

ACHIEVER[®] Series



**Featuring Industry Standard
R-410A Refrigerant**

R-410A

Features

The Ruud *Achiever*[®] Series RQNM/RQPM/RQRM- Package Heat Pumps can provide year-round heating and cooling comfort for residential, multi-family and light commercial applications.

The following additional features, plus its energy-saving characteristics, make the RQNM/RQPM/RQRM- Package Heat Pumps an excellent choice for new construction or upgrading your present system.

- Hi-Static Capability
- Indoor Coil access for easy cleaning
- Slide-out Indoor Blower for easy motor and blower maintenance
- Slide-out Drain Pan for easy access and cleaning
- Round Horizontal Supply & Return for application adaptability
- Duct Collars provided
- Condensate Trap provided
- Scroll Compressor
- Copper Tube/Aluminum Fin Coils
- Powder painted louvered steel cabinet protects coil from yard hazard damage
- Painted Base Pan
- Easily accessible Gauge Ports
- Spacious Control Box for easy accessibility
- Power and control wiring are kept separate
- Certified and rated under AHRI Standard 210
- U.L. listed
- Zero clearance to structure
- Electric Heat Factory or Field Installed

RQNM-

13 SEER Series

Nominal Sizes 2-5 Tons [7-17.6 kW]

RQPM-

14 SEER Series

Nominal Sizes 2-5 Tons [7-17.6 kW]

RQRM-

15/16 SEER Series

Nominal Sizes 2-5 Tons [7-17.6 kW]

GENERAL TERMS OF LIMITED WARRANTY

Ruud will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Compressor, 1 Phase, Residential ApplicationsTen (10) Years
 13 & 14 SEER, Commercial ApplicationsFive (5) Years
 Conditional Parts, 1 Phase, Residential Applications
 (Registration Required)Ten (10) Years
 1 & 3 Phase, Commercial Applications.....One (1) Year

<u>R</u>	<u>Q</u>	<u>N</u>	<u>M</u> — <u>A</u>	<u>036</u>	<u>J</u>	<u>K</u>	<u>010</u>	
RUUD	PRODUCT CLASSIFICATION	EFFICIENCY DESIGNATION (STANDARD)	DESIGN SERIES	FUTURE TECHNICAL VARIATIONS	NOMINAL COOLING CAPACITY	ELECTRICAL DESIGNATION	DRIVE PACKAGE	HEATING CAPACITY (FACTORY INSTALLED)
	Q = PACKAGE HEAT PUMP	N = 13 SEER P = 14 SEER R = 15/16 SEER	M = R-410A		024 = 24,000 BTU/H [7.03 kW] 030 = 30,000 BTU/H [8.79 kW] 036 = 36,000 BTU/H [10.55 kW] 037 = 36,000 BTU/H [10.55 kW] 042 = 42,000 BTU/H [12.31 kW] 043 = 43,000 BTU/H [12.60 kW] 048 = 48,000 BTU/H [14.07 kW] 049 = 48,000 BTU/H [14.07 kW] 060 = 60,000 BTU/H [17.58 kW]	J = 208-230V— 1PH—60 Hz C = 208-230V— 3PH—60 Hz (13 SEER ONLY)	K = DIRECT DRIVE	000 = No Resistance Heat 005 = 05 KW Resistance Heat 007 = 07 KW Resistance Heat 010 = 10 KW Resistance Heat 015 = 15 KW Resistance Heat 020 = 20 KW Resistance Heat

Price

Starting at:
\$

