

# RUUD SALES FACT SHEET

**R95T- SERIES**  
**95% A.F.U.E.†**  
**Models with Input Rates of**  
**40 to 115 kBTU**  
**[11.72 to 33.71 kW]**



## Ruud Achiever Plus® Series Multi position Gas Furnaces

### Features

- 95% residential gas furnace CSA certified
- 4 way multi-raise design
- PlusOne™ Diagnostics 7-Segment LED all units
- PlusOne™ Ignition System – DSI for reliability and longevity
- PlusOne™ Water Management System with patented Blocked Drain Sensor
- Heat exchanger is removable for improved serviceability. Primary is constructed of aluminized steel, secondary is constructed of stainless steel for maximum corrosion resistance and thermal fatigue reliability.
- Low profile “34 inch” cabinet ideal for space constrained installations.
- Blower Shelf design – serviceable in all furnace orientations
- Pre marked hoses – insures proper system drainage
- Vent with 2" or 3" PVC
- Replaceable Collector box
- Hemmed edges on cabinet and doors
- Constant Torque electrically commutated motor
- Quarter turn fasteners for tool less access
- Integrated control boards feature dip switches for easy system set up
- Self priming condensate trap
- Solid bottom included

### GENERAL TERMS OF LIMITED WARRANTY\*

Ruud will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Heat Exchanger . . . . . Limited Lifetime  
 Conditional Parts  
 (Registration Required) . . . . . Ten (10) Years

†A.F.U.E. (Annual Fuel Utilization Efficiency) calculated in accordance with Department of Energy test procedures.

\*For complete details of the Limited and Conditional Warranties, including applicable terms and conditions, contact your local contractor or the Manufacturer for a copy of the product warranty certificate.

| MODEL      | INPUT-BTU/HR [kW] ① | HEATING CAPACITY BTU/HR [kW] | HEATING CFM @ .2" [.049 kPa] W.C. E.S.P. [L/s] | COOLING CFM @ .5" [.124 kPa] W.C. E.S.P. [L/s] | APPROX. SHIPPING WEIGHT (LBS.) [kg] | PRICE |
|------------|---------------------|------------------------------|--|--|-------------------------------------|-------|
| R95T(-)040 | 42,000 [12.31]      | 41,000 [12.01]               | 982 [463]                                      | 1239 [585]                                     | 123.5 [56]                          |       |
| R95T(-)060 | 56,000 [16.41]      | 54,000 [15.83]               | 913 [431]                                      | 1227 [579]                                     | 128 [58]                            |       |
| R95T(-)070 | 70,000 [20.51]      | 68,000 [19.93]               | 1113 [525]                                     | 1198 [565]                                     | 132 [60]                            |       |
| R95T(-)085 | 84,000 [24.62]      | 82,000 [24.03]               | 1574 [743]                                     | 1833 [865]                                     | 147.5 [67]                          |       |
| R95T(-)100 | 98,000 [38.71]      | 95,000 [27.84]               | 1651 [779]                                     | 1975 [932]                                     | 152 [69]                            |       |
| R95T(-)115 | 112,000 [32.82]     | 108,000 [31.65]              | 1524 [719]                                     | 1748 [825]                                     | 165 [75]                            |       |

Note: Above data and specs are for upflow models.

[ ] Designates Metric Conversions





# SALES FACT SHEET

## R95T ACCESSORIES

| Description   | Part No.   | Price |
|---|------------|-------|
| Condensate Pump Kit   | 1PCB151TUL |       |
| External Bottom Filter (Upflow/Horizontal) Rack   | RXGF-CB    |       |
| External Side Filter Rack   | RXGF-CD    |       |
| External Downflow Top Filter Rack   | RXGF-CC    |       |
| Fossil Fuel Kit   | FXPF-F01   |       |
| Fossil Fuel Kit   | RXPF-F02   |       |
| Downflow/Horizontal Conversion Kit  | RXGY-CK    |       |
| Downflow/Horizontal Left Zero Clearance Conversion Kit                                      | RXGY-ZK    |       |
| Combustible Floor Base  | RXGC-B17   |       |
| Combustible Floor Base  | RXGC-B21   |       |
| Combustible Floor Base  | RXGC-B24   |       |
| Direct Vent Furnace Side Wall Vent 2" or 3"   | RXGY-G02   |       |
| LP Conversion Kit   | RXGJ-FP33  |       |
| Neutralizer Kit   | RXGY-A01   |       |
| Return Air Plenum   | RXGR-C17B  |       |
| Return Air Plenum   | RXGR-C21B  |       |
| Return Air Plenum   | RXGR-B24C  |       |
| Vent Termination Kit - Concentric Horizontal/Vertical (US & Canadian Installations) 3" Pipe | RXGY-E03A  |       |
| Vent Termination Kit - Concentric Horizontal/Vertical (US & Canadian Installations) 2" Pipe | RXGY-E02A  |       |
| Vent Termination Kit - Concentric Horizontal/Vertical (US Installation Only) 2" Pipe        | RXGY-E02   |       |
| Vent Termination Kit - Concentric Horizontal/Vertical (US Installation Only) 3" Pipe        | RXGY-E03   |       |
| Indoor Coil Casing  | RXBC-D17AI |       |
| Indoor Coil Casing  | RXBC-D21AI |       |
| Indoor Coil Casing  | RXBC-D24AI |       |
| Indoor Coil Casing  | RXBC-D21B1 |       |
| Combustion Air Drain Kit 2"   | RXGY-D05   |       |
| Combustion Air Drain Kit 3"   | RXGY-D06   |       |