



Dual-Flo

Two-Way Discharge Unit Cooler

The Dual-Flo unit cooler is designed for use in walk-in coolers and freezers to increase storage space. Its extra-low profile and two-way discharge permits mounting above aisle areas without sacrificing either headroom or proper air circulation. Walls are thus free for maximum utilization of shelving. It is ideal for convenience stores, supermarkets, restaurants and other low-ceiling type installations.

Air Defrost Models – 6,400 through 25,000 BTUH @ 10 Degree T.D.
Electric Defrost Models – 4,800 through 21,800 BTUH @ 10 Degree T.D.



Performance and Electrical Data

AIR DEFROST Models

	MODEL NUMBER	BTUH @ +25°F S.T.		CFM	SP* MOTOR AMPS		PSC* MOTOR AMPS		ECM* MOTOR AMPS	
		10°T.D.	15°T.D.		115/1	208-230/1	115/1	208-230/1	115/1	208-230/1
8 FPI	DFA38-75	7,500	11,250	1,460	3.3	1.7	1.5	0.9	1.74	0.87
	DFA38-88	8,800	13,200	1,310	3.3	1.7	1.5	0.9	1.74	0.87
	DFA38-98	9,800	14,700	1,200	3.3	1.7	1.5	0.9	1.74	0.87
	DFA48-112	11,200	16,800	2,120	4.4	2.2	2.0	1.2	2.32	1.16
	DFA48-130	13,000	19,500	1,920	4.4	2.2	2.0	1.2	2.32	1.16
	DFA48-150	15,000	22,500	1,760	4.4	2.2	2.0	1.2	2.32	1.16
	DFA58-162	16,200	24,300	2,320	5.5	2.8	2.5	1.5	2.90	1.45
	DFA48-210	21,000	31,500	1,820	4.4	2.2	2.0	1.2	2.32	1.16
	DFA58-230	23,000	34,500	2,650	5.5	2.8	2.5	1.5	2.90	1.45
	DFA68-250	25,000	37,500	2,970	6.6	3.3	3.0	1.8	3.48	1.74
6 FPI	DFA36-64	6,400	9,600	1,530	3.3	1.7	1.5	0.9	1.74	0.87
	DFA36-82	8,200	12,300	1,380	3.3	1.7	1.5	0.9	1.74	0.87
	DFA36-93	9,300	13,950	1,270	3.3	1.7	1.5	0.9	1.74	0.87
	DFA46-100	10,000	15,000	2,210	4.4	2.2	2.0	1.2	2.32	1.16
	DFA46-123	12,300	18,450	2,020	4.4	2.2	2.0	1.2	2.32	1.16
	DFA46-140	14,000	21,000	1,860	4.4	2.2	2.0	1.2	2.32	1.16
	DFA56-157	15,700	23,500	2,440	5.5	2.8	2.5	1.5	2.90	1.45
	DFA46-190	19,000	28,500	1,870	4.4	2.2	2.0	1.2	2.32	1.16
	DFA56-208	20,800	31,200	2,760	5.5	2.8	2.5	1.5	2.90	1.45
	DFA66-232	23,200	34,800	3,100	6.6	3.3	3.0	1.8	3.48	1.74

SP* = Shaded Pole motor(s) PSC* = Permanent Split Capacitor(s) ECM* = Electronically Commutated Motor(s)
Standard voltage for DFA models is 115/1/60

ELECTRIC DEFROST Models

	MODEL NUMBER	BTUH @ 10°T.D.		CFM	SP* MOTOR		PSC* MOTOR		ECM* MOTOR		DEFROST WATTS	DEFROST AMPS	
		-20°S.T.	+20°S.T.		115/1	208-230/1	115/1	208-230/1	115/1	208-230/1		208-230/1	460/1
6 FPI	DFE36-53	5,300	6,360	1530	3.3	1.7	1.5	0.9	1.74	0.87	2070	9.0	4.5
	DFE36-62	6,200	7,440	1380	3.3	1.7	1.5	0.9	1.74	0.87	2070	9.0	4.5
	DFE36-69	6,900	8,200	1270	3.3	1.7	1.5	0.9	1.74	0.87	2070	9.0	4.5
	DFE46-77	7,700	9,240	2210	4.4	2.2	2.0	1.2	2.32	1.16	2990	13.0	6.5
	DFE46-90	9,000	10,800	2020	4.4	2.2	2.0	1.2	2.32	1.16	2990	13.0	6.5
	DFE46-100	10,000	12,000	1860	4.4	2.2	2.0	1.2	2.32	1.16	2990	13.0	6.5
	DFE56-125	12,500	15,000	2440	5.5	2.8	2.5	1.5	2.90	1.45	3910	17.0	8.5
	DFE46-140	14,000	16,800	1870	4.4	2.2	2.0	1.2	2.32	1.16	3910	17.0	8.5
	DFE56-160	16,000	19,200	2760	5.5	2.8	2.5	1.5	2.90	1.45	3910	17.0	8.5
	DFE66-218	21,800	23,200	3100	6.6	3.3	3.0	1.8	3.48	1.74	3910	17.0	8.5
4 FPI	DFE34-48	4,800	5,760	1600	3.3	1.7	1.5	0.9	1.74	0.87	2070	9.0	4.5
	DFE34-58	5,800	6,960	1470	3.3	1.7	1.5	0.9	1.74	0.87	2070	9.0	4.5
	DFE34-65	6,500	7,800	1360	3.3	1.7	1.5	0.9	1.74	0.87	2070	9.0	4.5
	DFE44-72	7,200	8,640	2310	4.4	2.2	2.0	1.2	2.32	1.16	2990	13.0	6.5
	DFE44-84	8,400	10,080	2130	4.4	2.2	2.0	1.2	2.32	1.16	2990	13.0	6.5
	DFE44-95	9,500	11,400	1980	4.4	2.2	2.0	1.2	2.32	1.16	2990	13.0	6.5
	DFE54-115	11,500	13,800	2580	5.5	2.8	2.5	1.5	2.90	1.45	3910	17.0	8.5
	DFE44-128	12,800	15,360	1930	4.4	2.2	2.0	1.2	2.32	1.16	3910	17.0	8.5
	DFE54-145	14,500	17,400	2870	5.5	2.8	2.5	1.5	2.90	1.45	3910	17.0	8.5
	DFE64-173	17,300	20,760	3270	6.6	3.3	3.0	1.8	3.48	1.74	3910	17.0	8.5

SP* = Shaded Pole motor(s) PSC* = Permanent Split Capacitor(s) ECM* = Electronically Commutated Motor(s)
230V/1 motors are suitable for 208V operation. Standard voltage for DFE models is 208-230/1/60

Physical Data

AIR DEFROST Models


	MODEL	DIMENSIONS(IN)					TXV	CONNECTIONS(IN)		SHIP WT.
		L	W	H	A	B		LIQ. (ODS)	SUCT. (ODS)	
8 FPI	DFA38-75	58-1/2	28-3/4	9	24	24	EXT	1/2	5/8	95
	DFA38-88	58-1/2	28-3/4	9	24	24	EXT	1/2	5/8	100
	DFA38-98	58-1/2	28-3/4	9	24	24	EXT	1/2	5/8	105
	DFA48-112	82-1/2	28-3/4	9-3/4	36	36	EXT	1/2	7/8	125
	DFA48-130	82-1/2	28-3/4	9-3/4	36	36	EXT	1/2	7/8	130
	DFA48-150	82-1/2	28-3/4	9-3/4	36	36	EXT	1/2	7/8	135
	DFA58-162	106-1/2	28-3/4	9-3/4	48	48	EXT	1/2	7/8	150
	DFA48-210	106-1/2	28-3/4	11-1/4	48	48	EXT	1/2	7/8	155
	DFA58-230	106-1/2	28-3/4	11-1/4	48	48	EXT	1/2	7/8	165
DFA68-250	106-1/2	28-3/4	11-1/4	48	48	EXT	1/2	1-1/8	185	
6 FPI	DFA36-64	58-1/2	28-3/4	9	24	24	EXT	1/2	5/8	90
	DFA36-82	58-1/2	28-3/4	9	24	24	EXT	1/2	5/8	95
	DFA36-93	58-1/2	28-3/4	9	24	24	EXT	1/2	5/8	100
	DFA46-100	82-1/2	28-3/4	9-3/4	36	36	EXT	1/2	7/8	120
	DFA46-123	82-1/2	28-3/4	9-3/4	36	36	EXT	1/2	7/8	125
	DFA46-140	82-1/2	28-3/4	9-3/4	36	36	EXT	1/2	7/8	130
	DFA56-157	106-1/2	28-3/4	9-3/4	48	48	EXT	1/2	7/8	145
	DFA46-190	106-1/2	28-3/4	11-1/4	48	48	EXT	1/2	7/8	150
	DFA56-208	106-1/2	28-3/4	11-1/4	48	48	EXT	1/2	7/8	160
DFA66-232	106-1/2	28-3/4	10-1/4	48	48	EXT	1/2	1-1/8	180	

ELECTRIC DEFROST Models

	MODEL	DIMENSIONS(IN)					TXV	CONNECTIONS(IN)		SHIP WT.
		L	W	H	A	B		LIQ. (ODS)	SUCT. (ODS)	
6 FPI	DFE36-53	58-1/2	28-3/4	9	24	24	EXT	1/2	5/8	95
	DFE36-62	58-1/2	28-3/4	9	24	24	EXT	1/2	5/8	100
	DFE36-69	58-1/2	28-3/4	9	24	24	EXT	1/2	5/8	105
	DFE46-77	82-1/2	28-3/4	9-3/4	36	36	EXT	1/2	7/8	125
	DFE46-90	82-1/2	28-3/4	9-3/4	36	36	EXT	1/2	7/8	130
	DFE46-100	82-1/2	28-3/4	9-3/4	36	36	EXT	1/2	7/8	135
	DFE56-125	106-1/2	28-3/4	9-3/4	48	48	EXT	1/2	7/8	150
	DFE46-140	106-1/2	28-3/4	11-1/4	48	48	EXT	1/2	7/8	155
	DFE56-160	106-1/2	28-3/4	11-1/4	48	48	EXT	1/2	7/8	165
	DFE66-218	106-1/2	28-3/4	11-1/4	48	48	EXT	1/2	1-1/8	185
4 FPI	DFE34-48	58-1/2	28-3/4	9	24	24	EXT	1/2	5/8	90
	DFE34-58	58-1/2	28-3/4	9	24	24	EXT	1/2	5/8	95
	DFE34-65	58-1/2	28-3/4	9	24	24	EXT	1/2	5/8	100
	DFE44-72	82-1/2	28-3/4	9-3/4	36	36	EXT	1/2	7/8	120
	DFE44-84	82-1/2	28-3/4	9-3/4	36	36	EXT	1/2	7/8	125
	DFE44-95	82-1/2	28-3/4	9-3/4	36	36	EXT	1/2	7/8	130
	DFE54-115	106-1/2	28-3/4	9-3/4	48	48	EXT	1/2	7/8	145
	DFE44-128	106-1/2	28-3/4	11-1/4	48	48	EXT	1/2	7/8	151
DFE54-145	106-1/2	28-3/4	11-1/4	48	48	EXT	1/2	7/8	160	
DFE64-173	106-1/2	28-3/4	11-1/4	48	48	EXT	1/2	1-1/8	180	

Features

- Flush-to-the-ceiling mounting - Providing extra storage room
- Two-way air flow for even air circulation and consistent temperature
- Hinged drain pan for easy service access and cleaning
- Quiet operation - Ideal for use in rooms with glass display doors




Energy Savings Analysis

Motor Change	Standard Motor Power Watts/Mtr	"Change to" Motor Power Watts/Mtr	Power Reduction Watts/Mtr	Run Time Hrs/Day	Motor Energy Savings kWh/Yr	Motor Energy Savings \$/Yr	Reduced Box Load MBTU/Yr	Cond. Unit EER	Cond. Unit Energy Savings kWh/Yr	Cond. Unit Energy Savings \$/Yr	Total Savings \$/Yr	Pay back Yrs
SP to PSC	75	51	24	22	193	19	658	5.2	126	13	32	1.0
SP to EC	75	35	40	22	321	32	1,096	5.2	211	21	53	2.0
PSC to EC	51	35	16	22	128	13	438	5.2	84	8	21	3.4

16 Watt SP, PSC and ECM (SP = Shaded Pole Motor, PSC = Permanent Split Capacitor Motor, EC = Electronically Commutated Motor)
Subtract 6% from total savings for medium temperature 24 run hours per day.

MODEL NUMBER NOMENCLATURE



Due to continuing product development, specifications are subject to change without notice.

